

sensIQ S inox



Product code 4007841034962

E-Nr. 535940630

- 4x pyro system
- UV-resistant plastic
- Including corner wall mount
- Remote control RC9 included
- Smart Remote remote control optional

neva
lux

114 x 74 x 128 mm



Technical Data

IDENTIFICATION			
Variant	inox	Segment-by-segment masking	Yes
Version	Motion detectors	Electronic scalability	No
Type of accessory	Corner adapter	Mechanical scalability	Yes
DIMENSIONS		Range detail	Reach adjustable from 2 - 20 m in 3 directions (100° in each)
Dimensions L x W x H	114 x 74 x 128 mm	Radial range	r = 4 m (42 m²)
ELECTRICAL		Tangential range	r = 20 m (1047 m²)
Mains connection	100 – 240 V , 50 / 60 Hz	Switching zones	1360 switching zones
Switching output 1 resistive	2000 W	Mounting height	2,00 – 5,00 m
Supply voltage detail	500 VA max., 120 V	Optimal mounting height	2 m
SENSOR TECHNOLOGY		CONNECTIVITY	
Sensor technology	passive infrared	Networking	Yes
Detection angle	300 °	LIGHTING TECHNOLOGY	
Opening angle	90 °	Constant light regulation	No
Sneak-under protection	Yes	SETTINGS	
		Twilight setting	2 – 2000 lx
		Time setting	5 sec – 15 min
		Base light function	No
		With remote control	Yes
		Twilight setting teach	Yes
		HOUSING & MATERIAL	
		Protection class (IP)	IP54
		Ambient temperature	-20 – 50 °C
		Mounting location	corner wall
		Application location	Indoors Outdoors
		Mounting type	Surface wiring
		Material	Plastic
		Colour	Silver
		SCOPE OF DELIVERY & WARRANTY	
		Manufacturer warranty	5 years
		CERTIFICATES & EPREL	
		Certificates	VDE

sensIQ S inox

Product code **4007841034962**
E-Nr. **535940630**

Illustrations

MOUNTING HEIGHT

2,00 – 5,00 m BEREICH	2 m OPTIMAL
--------------------------	----------------

sensIQ S inox

Product code **4007841034962**
E-Nr. **535940630**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841007638	Fernbedienung RC9	Other
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841034962

E-Number

535940630

Typ

sensIQ S inox

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss