L 170 S

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841645311
E-Nr. 924350279

- Intelligent soft light start
- Optional basic lighting level 0 - 50 %
- High-quality designer trim panel in stainless steel
- 4-hour manual override (optional)

340 x 220 x 150 mm



L 170 S

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841645311
E-Nr. 924350279

Technical Data

DIMENSIONS

Dimensions L × W × H	340 x 220 x 150 mm

ELECTRICAL

Mains connection	230 – 240 V , 60 / 60 Hz
Power	100 W

SENSOR TECHNOLOGY

Sensor technology	passive infrared
With motion detector	Yes
Detection angle	180 °
Opening angle	90 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No
Mechanical scalability	No
Tangential range	r = 12 m (226 m²)

CONNECTIVITY

Control technology	On/Off-Leuchte

LIGHTING TECHNOLOGY

With illuminant	No
Illuminant	All-purpose lamp
Base	E27
Soft light start	Yes
Continuous light	selectable, 4h

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 sec – 15 min

HOUSING & MATERIAL

Protection class (IP)	IP43
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Stainless steel
Cover material	Glass transparent

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	3 years

L 170 S

SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841645311**
E-Nr. **924350279**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841001513	**Ersatzglas für L 170 S**	Spare Part
	4007841002190	**Ersatz-Grundkörper L 170 S / L 190 S**	Spare Part

ORDERING INFORMATION

Art.-Nr.	4007841645311
EAN	4007841645311
E-Number	924350279
Typ	**L 170 S**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss