

# RS PRO Connect R30 Q warmweiss



Product code **4007841057220**

E-Nr. **941301499**

- Including STEINEL LED system
- Interconnectable and adjustable via Bluetooth
- Impact-resistant material rated to IK07
- Backlight function
- Optional basic lighting level 10 - 50 %
- Optional main light level 50 - 100 %
- Optional emergency light

**neva**  
**lux**

55 x 350 x 350 mm



RS PRO Connect R30 Q warmweiss

Product code **4007841057220**  
E-Nr. **941301499**

Technical Data

| IDENTIFICATION             |                                         | CONNECTIVITY                   |                         |                                                                                                                                             |             |
|----------------------------|-----------------------------------------|--------------------------------|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| Variant                    | warm white                              | Networking                     | Yes                     | Twilight setting                                                                                                                            | 2 – 2000 lx |
| DIMENSIONS                 |                                         | Type of networking             |                         | Time setting                                                                                                                                |             |
| Dimensions L x W x H       | 55 x 350 x 350 mm                       | Master/slave                   |                         | 5 sec – 30 min                                                                                                                              |             |
| ELECTRICAL                 |                                         | LIGHTING TECHNOLOGY            |                         | Base light function                                                                                                                         |             |
| Mains connection           | 220 – 240 V / 50 – 60 Hz                | Colour temperature             | 3000 K                  | Yes                                                                                                                                         |             |
| Power                      | 24,5 W                                  | LED colour deviation           | SDCM3                   | Base light function detail                                                                                                                  |             |
| Own consumption            | 0,5 W                                   | Colour rendering index         | 80-89                   | LED Backlight                                                                                                                               |             |
| SENSOR TECHNOLOGY          |                                         | With illuminant                | Yes, STEINEL LED system | Base light function time                                                                                                                    |             |
| Sensor technology          | High frequency                          | Illuminant                     | LED cannot be replaced  | 10-30 min, all night                                                                                                                        |             |
| Transmission power         | < 1 mW                                  | Base                           | without                 | Functions                                                                                                                                   |             |
| HF technology              | 5,8 GHz                                 | LED cooling system             | Passive Thermo Control  | Group parameterisation,<br>Manual ON / ON-OFF,<br>Master/slave override,<br>Neighbouring-group<br>function, Presence function,<br>Backlight |             |
| With motion detector       | Yes                                     | Soft light start               | Yes                     |                                                                                                                                             |             |
| Detection                  | also through glass, wood and stud walls | Continuous light               | selectable              |                                                                                                                                             |             |
| Detection angle            | 360 °                                   | Luminous flux                  | 3070 lm                 | Settings via                                                                                                                                |             |
| Opening angle              | 160 °                                   | LIFETIME                       |                         | Bluetooth                                                                                                                                   |             |
| Segment-by-segment masking | Yes                                     | LED lifetime max. °C           | 50000 h                 | With remote control                                                                                                                         |             |
| Electronic scalability     | Yes                                     | Luminous flux decline per LM80 | L80B50                  | No                                                                                                                                          |             |
| Mechanical scalability     | No                                      | LED lifespan (25 °C)           | 60000 h                 | HOUSING & MATERIAL                                                                                                                          |             |
| Radial range               | Ø 10 m (79 m²)                          | SETTINGS                       |                         | Impact resistance                                                                                                                           | IK07        |
|                            |                                         | Twilight switch                | Yes                     | Protection class (IP)                                                                                                                       | IP40        |
|                            |                                         |                                |                         | Protection class                                                                                                                            | II          |
|                            |                                         |                                |                         | Ambient temperature                                                                                                                         | -20 – 40 °C |
|                            |                                         |                                |                         | Housing material                                                                                                                            | Plastic     |
|                            |                                         |                                |                         | Cover material                                                                                                                              | PC, opal    |
|                            |                                         | SCOPE OF DELIVERY & WARRANTY   |                         |                                                                                                                                             |             |
|                            |                                         |                                |                         | Manufacturer warranty                                                                                                                       | 5 years     |

RS PRO Connect R30 Q warmweiss

Product code **4007841057220**  
E-Nr. **941301499**

Accessories

| ARTICLE NUMBER                                                                                 | DESCRIPTION            | CATEGORY  |
|------------------------------------------------------------------------------------------------|------------------------|-----------|
|  4007841064143 | Notlicht-Modul R-Serie | Accessory |

ORDERING INFORMATION

Art.-Nr.

4007841057220

E-Number

941301499

Typ

RS PRO Connect R30 Q warmweiss

neva  
lux

nevalux AG  
Neugrütstrasse 2  
8610 Uster  
+41 44 508 78 78  
info@nevalux.swiss