HF 360 COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079512
E-Nr. 535930710

steinel

94 x 120 x 120 mm



HF 360 COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079512
E-Nr. 535930710

Technical Data

IDENTIFICATION

Version	Presence detector

DIMENSIONS

Dimensions L × W × H	94 x 120 x 120 mm

ELECTRICAL

Mains connection	230 V / 50 – 60 Hz

SENSOR TECHNOLOGY

Max. mounting height	3,50 m
Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	5,8 GHz
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	140 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	No
Range detail	1 or 2 detection directions can be masked out by stickers for adjustment to the room situation.
Radial range	Ø 12 m (113 m²)
Tangential range	Ø 12 m (113 m²)
Mounting height	2,50 – 3,50 m
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Type of networking	Master/master Master/slave

LIGHTING TECHNOLOGY

Soft light start	No
Continuous light	selectable
Constant light regulation	No

SETTINGS

Twilight switch	Yes
Twilight setting	10 – 1000 lx
Time setting	30 s – 30 Min.
Base light function	No
Main light adjustable	No
Functions	Normal / test mode Semi-/fully automatic Pushbutton / switch mode Manual ON / ON-OFF
Settings via	Remote control DIP switches Potentiometers Smart Remote
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	from -25 up to 55 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	In-ceiling installation
Material	Plastic
Application room	Indoors WC / washroom function room / ancillary room kitchenette stairwell
Colour	white
RAL colour	9010

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No


HF 360 COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079512**
E-Nr. **535930710**

Illustrations

TECHNICAL DRAWINGS



94 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 3,50 m	2,8 m	3,50 m
BEREICH	OPTIMAL	MAX


HF 360 COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079512
E-Nr. 535930710


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/master interconnection circuit diagram

HF 360 COM1 - in-ceiling installation


PRESENCE DETECTOR

EAN 4007841079512
E-Nr. 535930710


Highlights



Optional remote controls



Optional surface-mounting adapter



Optional guard cage



HF ceiling adapter for installation in suspended ceilings

HF 360 COM1 - in-ceiling installation

PRESENCE DETECTOR

EAN **4007841079512**
E-Nr. **535930710**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841003036	**Control PRO Schutzkorb**	Accessory
	4007841009151	**Smart Remote**	Accessory
	4007841559410	**Service Fernbedienung RC8**	Accessory

ORDERING INFORMATION

Art.-Nr.	079512
EAN	4007841079512
E-Number	535930710
Typ	**HF 360 COM1 - in-ceiling installation**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss