XLED PRO Wide eNet - white

SENSOR-SWITCHED LED FLOODLIGHT

EAN 4007841010218

- Including STEINEL LED system
- Intelligent LED cooling system
- Optional basic lighting level
- UV resistant material
- Wireless interconnection
- Remote control RC9 included
- Smart Remote remote control optional

126 x 265 x 188 mm



XLED PRO Wide eNet - white

SENSOR-SWITCHED LED FLOODLIGHT

EAN 4007841010218

Technical Data

IDENTIFICATION

Variant	eNet - white

DIMENSIONS

Dimensions L × W × H	126 x 265 x 188 mm

ELECTRICAL

Mains connection	220 – 240 V , 50 / 60 Hz
Power	24,8 W

SENSOR TECHNOLOGY

Max. mounting height	6,00 m
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	240 °
Opening angle	180 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Tangential range	r = 12 m (302 m²)

CONNECTIVITY

Networking	Yes
Control technology	On/Off-Leuchte

LIGHTING TECHNOLOGY

Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
LED cooling system	Passive Thermo Control
Luminous flux	2400 lm

LIFETIME

LED lifetime max. °C	50000 h

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 1000 lx

HOUSING & MATERIAL

Impact resistance	IK03
Protection class (IP)	IP54
Protection class	I
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

XLED PRO Wide eNet - white

SENSOR-SWITCHED LED FLOODLIGHT

EAN 4007841010218

Illustrations

MOUNTING HEIGHT

6,00 m
MAX

XLED PRO Wide eNet - white

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841010218**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841032821	**eNet Funk Handsender 2-fach**	Accessory
	4007841032838	**eNet Schaltaktor**	Accessory

ORDERING INFORMATION

Art.-Nr.	4007841010218
EAN	4007841010218
Typ	**XLED PRO Wide eNet - white**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss