

L 630 LED silber

neva
lux

Product code **4007841020385**

E-Nr. **924361002**

- Including STEINEL LED system
- Optional basic lighting level 10 %
- Sensor with 4 intelligent programmes
- UV-resistant plastic
- Impact-resistant material rated to IK07
- Including sheet of self-adhesive house numbers
- 4-hour manual override (optional)

neva
lux

364 x 211 x 65 mm



L 630 LED silber

Product code **4007841020385**
E-Nr. **924361002**

Technical Data

IDENTIFICATION		Tangential range		r = 8 m (201 m²)		SETTINGS	
Variant	Silver	LIGHTING TECHNOLOGY				Twilight switch	Yes
DIMENSIONS		Colour temperature		3000 K		Twilight setting	2 – 2000 lx
Dimensions L x W x H	364 x 211 x 65 mm	LED colour deviation		SDCM3		Time setting	5 sec – 15 min
ELECTRICAL		Colour rendering index		80-89		HOUSING & MATERIAL	
Mains connection	220 – 240 V , 50 / 50 Hz	With illuminant		Yes, STEINEL LED system		Impact resistance	IK07
Power	8,2 W	Illuminant		LED cannot be replaced		Protection class (IP)	IP44
SENSOR TECHNOLOGY		Base		without		Protection class	I
Sensor technology	passive infrared	LED cooling system		Passive Thermo Control		Ambient temperature	-20 – 50 °C
With motion detector	Yes	Soft light start		Yes		Housing material	Plastic
Detection angle	360 °	Continuous light		selectable, 4h		Cover material	Plastic, opal
Sneak-under protection	Yes	Luminous flux		663 lm		SCOPE OF DELIVERY & WARRANTY	
Segment-by-segment masking	Yes	LIFETIME				Manufacturer warranty	3 years
Electronic scalability	No	LED lifetime max. °C		50000 h		House number sheet included	Yes
Mechanical scalability	No	Luminous flux decline per LM80		L70B10			

L 630 LED silber

Product code **4007841020385**
E-Nr. **924361002**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841009038	Ersatz-Minisensor silber	Spare Part

ORDERING INFORMATION

Art.-Nr.

4007841020385

E-Number

924361002

Typ

L 630 LED silber

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss