HF 360-2 KNX - Surface wiring

PRESENCE DETECTOR

EAN 4007841064860
E-Nr. 535931608

steinel

57 x 123 x 123 mm



HF 360-2 KNX - Surface wiring

PRESENCE DETECTOR

EAN 4007841064860
E-Nr. 535931608

Technical Data

IDENTIFICATION

Version	Presence detector

DIMENSIONS

Dimensions L × W × H	57 x 123 x 123 mm

ELECTRICAL

Mains connection	30 V
Supply voltage detail	KNX bus

SENSOR TECHNOLOGY

Max. mounting height	4,00 m
Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	5,8 GHz
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	140 °
Sneak-under protection	Yes
Segment-by-segment masking	No
Electronic scalability	Yes
Mechanical scalability	No
Range detail	1 or 2 detection directions can be masked out by stickers for adjustment to the room situation.
Radial range	Ø 12 m (113 m²)
Tangential range	Ø 12 m (113 m²)
Mounting height	2,50 – 4,00 m
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Type of networking	Master/master Master/slave
KNX functions	Comfort Photo-cell controller Individual pyro evaluation Basic light level function Light level HVAC output Constant-lighting control Light output 4x Humidity output Presence output Day / night function Dewpoint Temperature output Logic gate
With bus coupler	Yes
Networking via	KNX

LIGHTING TECHNOLOGY

Soft light start	Yes
Continuous light	selectable
Constant light regulation	Yes

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 1000 lx
Time setting	10 s – 1092 Min.
Base light function	Yes
Main light adjustable	0 - 100 %
Settings via	ETS software Bluetooth Bus
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	from -25 up to 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Surface wiring
Material	Plastic
Application room	Indoors WC / washroom function room / ancillary room kitchenette stairwell
Colour	white
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No


HF 360-2 KNX - Surface wiring

PRESENCE DETECTOR

EAN **4007841064860**
E-Nr. **535931608**

Illustrations

TECHNICAL DRAWINGS



57 x 123 x 123 mm

MOUNTING HEIGHT

2,50 – 4,00 m	2,8 m	4,00 m
BEREICH	OPTIMAL	MAX

HF 360-2 KNX - Surface wiring

PRESENCE DETECTOR

EAN 4007841064860
E-Nr. 535931608

Highlights



UV-resistant plastic

HF 360-2 KNX - Surface wiring

PRESENCE DETECTOR

EAN **4007841064860**
E-Nr. **535931608**

Accessories

ORDERING INFORMATION

Art.-Nr.	064860
EAN	4007841064860
E-Number	535931608
Typ	**HF 360-2 KNX - Surface wiring**

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss