L 170 S

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841645311
E-Nr. 924350279

- Intelligent soft light start
- Optional basic lighting level 0 - 50 %
- High-quality designer trim panel in stainless steel
- 4-hour manual override (optional)

steinel

340 x 220 x 150 mm



L 170 S

SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841645311**
E-Nr. **924350279**

Technical Data

DIMENSIONS

Dimensions L × W × H	**340 x 220 x 150 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Power	**100 W**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
With motion detector	**Yes**
Detection angle	**180 °**
Opening angle	**90 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**No**
Mechanical scalability	**No**
Tangential range	**r = 12 m (226 m²)**

LIGHTING TECHNOLOGY

With illuminant	**No**
Illuminant	**All-purpose lamp**
Base	**E27**
Soft light start	**Yes**
Continuous light	**selectable, 4h**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**5 s – 15 min**

HOUSING & MATERIAL

Protection class (IP)	**IP43**
Protection class	**II**
Ambient temperature	**-20...+40 °C**
Housing material	**Stainless steel**
Cover material	**Clear glass**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**3 years**

L 170 S

SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841645311**
E-Nr. **924350279**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841001513	**Ersatzglas für L 170 S**	Spare Part
	4007841002190	**Ersatz-Grundkörper L 170 S / L 190 S**	Spare Part

ORDERING INFORMATION

Art.-Nr.	4007841645311
EAN	4007841645311
E-Number	924350279
Typ	**L 170 S**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss