# IS 2180-5 black

**MOTION DETECTOR**

EAN 4007841605711

- UV-resistant plastic
- Including corner wall mount

steinel

120 x 78 x 55 mm



# IS 2180-5 black

**MOTION DETECTOR**

EAN **4007841605711**

# Technical Data

## IDENTIFICATION

| | |
|---|---|
| Variant | **black** |
| Version | **Motion detectors** |

## DIMENSIONS

| | |
|---|---|
| Dimensions L × W × H | **120 x 78 x 55 mm** |

## ELECTRICAL

| | |
|---|---|
| Mains connection | **230 V / 50 – 60 Hz** |
| Switching output 1 resistive | **1000 W** |

## SENSOR TECHNOLOGY

| | |
|---|---|
| Sensor technology | **passive infrared** |
| Detection angle | **180 °** |
| Opening angle | **90 °** |
| Sneak-under protection | **Yes** |
| Segment-by-segment masking | **Yes** |
| Electronic scalability | **No** |
| Mechanical scalability | **No** |
| Tangential range | **r = 8 m (101 m²) / r = 20 m (628 m²)** |
| Switching zones | **504 switching zones** |
| Optimal mounting height | **2,0 m** |

## CONNECTIVITY

| | |
|---|---|
| Networking | **Yes** |

## LIGHTING TECHNOLOGY

| | |
|---|---|
| Constant light regulation | **No** |

## SETTINGS

| | |
|---|---|
| Twilight setting | **2 – 2000 lx** |
| Time setting | **5 s – 15 min** |
| Base light function | **No** |
| With remote control | **No** |
| Twilight setting teach | **No** |

## HOUSING & MATERIAL

| | |
|---|---|
| Protection class (IP) | **IP54** |
| Ambient temperature | **-20…+50 °C** |
| Mounting location | **corner, wall** |
| Application location | **Outdoors** |
| Mounting type | **Surface mounting** |
| Material | **Plastic** |
| Colour | **Black** |
| RAL colour | **9005** |

## SCOPE OF DELIVERY & WARRANTY

| | |
|---|---|
| Manufacturer warranty | **5 years** |

# IS 2180-5 black

**MOTION DETECTOR**

EAN **4007841605711**

## Illustrations

**MOUNTING HEIGHT**

2,0 m

OPTIMAL

# IS 2180-5 black

**MOTION DETECTOR**

EAN **4007841605711**

## Accessories

**ORDERING INFORMATION**

| | |
|---|---|
| Art.-Nr. | 4007841605711 |
| EAN | 4007841605711 |
| Typ | **IS 2180-5 black** |

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss