IS 2180-5 white

MOTION DETECTOR

EAN 4007841605018

- UV-resistant plastic
- Including corner wall mount

steinel

120 x 78 x 55 mm



IS 2180-5 white

MOTION DETECTOR

EAN **4007841605018**

Technical Data

IDENTIFICATION

Variant	**white**
Version	**Motion detectors**

DIMENSIONS

Dimensions L × W × H	**120 x 78 x 55 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Switching output 1 resistive	**1000 W**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
Detection angle	**180 °**
Opening angle	**90 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**No**
Mechanical scalability	**No**
Tangential range	**r = 8 m (101 m²) / r = 20 m (628 m²)**
Switching zones	**504 switching zones**
Optimal mounting height	**2,0 m**

CONNECTIVITY

Networking	**Yes**

LIGHTING TECHNOLOGY

Constant light regulation	**No**

SETTINGS

Twilight setting	**2 – 2000 lx**
Time setting	**5 s – 15 min**
Base light function	**No**
With remote control	**No**
Twilight setting teach	**No**

HOUSING & MATERIAL

Protection class (IP)	**IP54**
Ambient temperature	**-20…+50 °C**
Mounting location	**corner, wall**
Application location	**Outdoors**
Mounting type	**Surface mounting**
Material	**Plastic**
Colour	**White**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

IS 2180-5 white

MOTION DETECTOR

EAN 4007841605018

Illustrations

MOUNTING HEIGHT

2,0 m

OPTIMAL

IS 2180-5 white

MOTION DETECTOR

EAN 4007841605018

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841605018
EAN	4007841605018
Typ	**IS 2180-5 white**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss