L 115 S Silver

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841657512

- Optional basic lighting level 0 - 50 %
- UV-resistant plastic
- Intelligent soft light start
- 4-hour manual override (optional)

steinel

330 x 215 x 257 mm



L 115 S Silver

SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841657512**

Technical Data

IDENTIFICATION

Variant	**Silver**

DIMENSIONS

Dimensions L × W × H	**330 x 215 x 257 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Power	**60 W**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
With motion detector	**Yes**
Detection angle	**240 °**
Opening angle	**120 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**No**
Mechanical scalability	**No**
Radial range	**r = 12 m (302 m²)**
Tangential range	**r = 12 m (302 m²)**

LIGHTING TECHNOLOGY

With illuminant	**No**
Illuminant	**All-purpose lamp**
Base	**E27**
Soft light start	**Yes**
Continuous light	**selectable, 4h**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**5 s – 15 min**
Base light function	**Yes**
Settings via	**Potentiometers**

HOUSING & MATERIAL

Impact resistance	**IK00**
Protection class (IP)	**IP44**
Protection class	**II**
Ambient temperature	**-20…+40 °C**
Housing material	**Plastic**
Cover material	**Clear glass**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**3 years**

L 115 S Silver

SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841657512**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841001681	**Ersatzglas für L 115 S**	Spare Part

ORDERING INFORMATION

Art.-Nr.	4007841657512
EAN	4007841657512
Typ	**L 115 S Silver**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss