Dual HF DIM

PRESENCE DETECTOR

EAN 4007841002985

- Optional remote controls
- Optional surface-mounting adapter
- Optional guard cage

steinel

120 x 120 x 75 mm



Dual HF DIM

PRESENCE DETECTOR

EAN 4007841002985

Technical Data

IDENTIFICATION

Variant	DIM
Version	Presence detector

DIMENSIONS

Dimensions L × W × H	120 x 120 x 75 mm

ELECTRICAL

Mains connection	230 V / 50 – 60 Hz
Number of ECGs DIM interface	50

SENSOR TECHNOLOGY

Sensor technology	High frequency
HF technology	5,8 GHz
Detection angle	360 °
Opening angle	140 °
Sneak-under protection	Yes
Electronic scalability	Yes
Mechanical scalability	No
Radial range	20 x 3 m (60 m²)
Tangential range	20 x 3 m (60 m²)
Mounting height	2,5 – 3,5 m
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Type of networking	Master/Slave, Master/Master

LIGHTING TECHNOLOGY

Constant light regulation	Yes

SETTINGS

Twilight setting	100 – 1000 lx
Time setting	30 s – 30 min
Base light function	Yes
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	-25…+50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Concealed mounting
Material	Plastic
Colour	White
RAL colour	9010

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

OTHER

Application, location, room	corridor, aisle

Dual HF DIM

PRESENCE DETECTOR

EAN 4007841002985

Illustrations

MOUNTING HEIGHT

2,5 – 3,5 m BEREICH	2,8 m OPTIMAL

Dual HF DIM

PRESENCE DETECTOR

EAN 4007841002985

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841003036	**Control PRO Schutzkorb**	Accessory
	4007841592806	**Nutzer Fernbedienung RC5**	Accessory
	4007841559410	**Service Fernbedienung RC8**	Accessory
	4007841000363	**Aufputz-Adapter Control Pro IP54 weiss**	Accessory
	4007841006600	**HF-Deckenadapter**	Accessory
	4007841009151	**Smart Remote**	Accessory

ORDERING INFORMATION

Art.-Nr.	4007841002985
EAN	4007841002985
Typ	**Dual HF DIM**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss