RS 14 L

SENSOR-SWITCHED INDOOR LIGHT

EAN 4007841731113
E-Nr. 920622049

- Long-life aluminium enclosure
- High-quality opal glass shade
- max. of 5 lights can be interconnected by cable
- Impact-resistant material rated to IK07
- Facility for connecting fan

steinel

280 x 110 mm



RS 14 L

SENSOR-SWITCHED INDOOR LIGHT

EAN **4007841731113**
E-Nr. **920622049**

Technical Data

DIMENSIONS

Dimensions Ø × H	**280 x 110 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Power	**60 W**
Switching output 1 resistive	**800 W**

SENSOR TECHNOLOGY

Sensor technology	**High frequency**
Transmission power	**< 1 mW**
With motion detector	**Yes**
Detection	**also through glass, wood and stud walls**
Detection angle	**360 °**
Opening angle	**160 °**
Electronic scalability	**Yes**
Mechanical scalability	**No**

LIGHTING TECHNOLOGY

With illuminant	**No**
Illuminant	**All-purpose lamp**
Base	**E27**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**5 s – 15 min**

HOUSING & MATERIAL

Impact resistance	**IK07**
Protection class (IP)	**IP44**
Protection class	**II**
Ambient temperature	**-20...+40 °C**
Housing material	**Aluminium**
Cover material	**Opal plastic**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

RS 14 L

SENSOR-SWITCHED INDOOR LIGHT

EAN **4007841731113**
E-Nr. **920622049**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841731113
EAN	4007841731113
E-Number	920622049
Typ	**RS 14 L**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss