L 825 LED iHF Anthracite

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841007164
E-Nr. 924352149

- Including STEINEL LED system
- Concealed iHF sensor
- Intelligent soft light start
- Optional basic lighting level 10 %
- High-quality aluminium
- 4-hour manual override (optional)

steinel

95 x 331 x 157 mm



L 825 LED iHF Anthracite

SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841007164**
E-Nr. **924352149**

Technical Data

IDENTIFICATION

Variant	**Anthracite**

DIMENSIONS

Dimensions L × W × H	**95 x 331 x 157 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Power	**12 W**

SENSOR TECHNOLOGY

Sensor technology	**iHF (intelligent high-frequency technology)**
Transmission power	**< 1 mW**
With motion detector	**Yes**
Detection angle	**160 °**
Sneak-under protection	**Yes**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**r = 5 m (35 m²)**
Tangential range	**r = 5 m (35 m²)**

LIGHTING TECHNOLOGY

Colour temperature	**3000 K**
LED colour deviation	**SDCM3**
Colour rendering index	**80 - 89**
With illuminant	**Yes, STEINEL LED system**
Illuminant	**LED cannot be replaced**
Base	**without**
LED cooling system	**Active and Passive Thermo Control**
Soft light start	**Yes**
Continuous light	**selectable, 4h**
Luminous flux	**400 lm**

LIFETIME

LED lifetime max. °C	**50000 h**
Luminous flux decline per LM80	**L70B10**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**5 s – 15 min**

HOUSING & MATERIAL

Protection class (IP)	**IP44**
Protection class	**II**
Ambient temperature	**-20...+50 °C**
Housing material	**Aluminium**
Cover material	**Opal plastic**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**3 years**

L 825 LED iHF Anthracite

SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841007164**
E-Nr. **924352149**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841007164
EAN	4007841007164
E-Number	924352149
Typ	**L 825 LED iHF Anthracite**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss