RS PRO 5850 LED Slave

INDOOR LIGHT

EAN 4007841007683
E-Nr. 941333979

- Including STEINEL LED system
- Optional remote control
- Interconnectable via DALI, max. 15 slaves?/master
- Impact-resistant material rated to IK07
- Intelligent swarm function

steinel

1583 x 105 x 105 mm



RS PRO 5850 LED Slave

INDOOR LIGHT

EAN 4007841007683
E-Nr. 941333979

Technical Data

IDENTIFICATION

Variant	Slave

DIMENSIONS

Dimensions L × W × H	1583 x 105 x 105 mm

ELECTRICAL

Mains connection	230 V / 50 – 60 Hz
Power	45 W

SENSOR TECHNOLOGY

Transmission power	< 1 mW
With motion detector	No

LIGHTING TECHNOLOGY

Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80 - 89
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Luminous flux	5570 lm

LIFETIME

LED lifetime max. °C	50000 h
Luminous flux decline per LM80	L70B10

SETTINGS

Twilight switch	No
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 min
Functions	Group parameterisation, Neighbouring-light function, Presence function

HOUSING & MATERIAL

Impact resistance	IK07
Protection class (IP)	IP66
Protection class	I
Ambient temperature	-20...+30 °C
Housing material	Plastic
Cover material	Opal plastic

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

RS PRO 5850 LED Slave

INDOOR LIGHT

EAN **4007841007683**
E-Nr. **941333979**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841008925	**RC10 für RS PRO 5800/5850 LED**	Accessory
	4007841009151	**Smart Remote**	Accessory

ORDERING INFORMATION

Art.-Nr.	4007841007683
EAN	4007841007683
E-Number	941333979
Typ	**RS PRO 5850 LED Slave**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss