RS PRO DL LED 15 W Slave - neutral white

INDOOR LIGHT

EAN 4007841007720

- Including STEINEL LED system
- Intelligent LED cooling system
- Ceiling-flush installation
- Interconnectable by cable ?(maximum of 10 units)
- Can only be set by optional remote control RC2

142.5 x 88 mm



RS PRO DL LED 15 W Slave - neutral white

INDOOR LIGHT

EAN 4007841007720

Technical Data

IDENTIFICATION

Variant	Slave - neutral white

DIMENSIONS

Dimensions Ø × H	142.5 x 88 mm

ELECTRICAL

Mains connection	230 V / 50 – 60 Hz
Power	15 W
Power detail	Only via Eltako ER12DX-UC with basic light function deactivated

SENSOR TECHNOLOGY

Transmission power	< 1 mW
With motion detector	No

LIGHTING TECHNOLOGY

Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80 - 89
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Luminous flux	838 lm

LIFETIME

LED lifetime max. °C	50000 h
Luminous flux decline per LM80	L70B10

SETTINGS

Twilight switch	No
Time setting	60 s – 60 min
Base light function time	10 min, 30 min, all night

HOUSING & MATERIAL

Impact resistance	IK00
Protection class (IP)	IP20
Protection class	II
Ambient temperature	-10…+40 °C
Housing material	Aluminium
Cover material	Opal plastic

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

RS PRO DL LED 15 W Slave - neutral white

INDOOR LIGHT

EAN 4007841007720

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841737818	**RS PRO Fernbedienung RC2**	Accessory
	4007841009151	**Smart Remote**	Accessory
	4007841013677	**Sanierungsblende für RS PRO DL LED 15 W**	Accessory

ORDERING INFORMATION

Art.-Nr.	4007841007720
EAN	4007841007720
Typ	**RS PRO DL LED 15 W Slave - neutral white**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss