US 360 DIM

PRESENCE DETECTOR

EAN 4007841007959

- Optional remote controls
- Optional surface-mounting adapter
- Optional guard cage

steinel

120 x 120 x 68 mm



US 360 DIM

PRESENCE DETECTOR

EAN **4007841007959**

Technical Data

IDENTIFICATION

Variant	**DIM**
Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**120 x 120 x 68 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Number of ECGs DIM interface	**50**

SENSOR TECHNOLOGY

Sensor technology	**Ultrasonic**
Detection angle	**360 °**
Sneak-under protection	**Yes**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**Ø 10 m (79 m²)**
Tangential range	**Ø 10 m (79 m²)**
Mounting height	**2,5 – 3,5 m**
Presence range	**Ø 6 m (28 m²)**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/Slave, Master/Master**

LIGHTING TECHNOLOGY

Constant light regulation	**Yes**

SETTINGS

Twilight setting	**100 – 1000 lx**
Time setting	**30 s – 30 min**
Base light function	**Yes**
With remote control	**No**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**-25...+55 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Concealed mounting**
Material	**Plastic**
Colour	**White**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

OTHER

Application, location, room	**classroom, One-person office, Open-plan office, conference room, side room, stairwell, washroom, wc, equipment room**

US 360 DIM

PRESENCE DETECTOR

EAN 4007841007959

Illustrations

MOUNTING HEIGHT

2,5 – 3,5 m BEREICH	2,8 m OPTIMAL

US 360 DIM

PRESENCE DETECTOR

EAN **4007841007959**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841592806	**Nutzer Fernbedienung RC5**	Accessory
	4007841559410	**Service Fernbedienung RC8**	Accessory
	4007841009151	**Smart Remote**	Accessory

ORDERING INFORMATION

Art.-Nr.	4007841007959
EAN	4007841007959
Typ	**US 360 DIM**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss