US 360 LiveLink

PRESENCE DETECTOR

EAN 4007841008444

- Optional surface-mounting adapter
- Optional guard cage

steinel

120 x 120 x 68 mm



US 360 LiveLink

PRESENCE DETECTOR

EAN **4007841008444**

Technical Data

IDENTIFICATION

Variant	**LiveLink**
Version	**Presence detector**
Model	**LiveLink**

DIMENSIONS

Dimensions L × W × H	**120 x 120 x 68 mm**

ELECTRICAL

Supply voltage detail	**DALI bus**
Livelink values	**Light level, Motion detection**

SENSOR TECHNOLOGY

Sensor technology	**Ultrasonic**
Detection angle	**360 °**
Opening angle	**180 °**
Sneak-under protection	**Yes**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**Ø 10 m (79 m²)**
Tangential range	**Ø 10 m (79 m²)**
Mounting height	**2,5 – 3,5 m**
Presence range	**Ø 6 m (28 m²)**
US technology	**40 kHz**
Optimal mounting height	**2,8 m**

CONNECTIVITY

With bus coupler	**Yes**

SETTINGS

Twilight setting	**10 – 1000 lx**
Time setting	**60 s – 60 min**
Settings via	**LiveLink app**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Concealed mounting**
Material	**Plastic**
Colour	**White**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

OTHER

Application, location, room	**classroom, One-person office, Open-plan office, conference room, side room, stairwell, washroom, wc, equipment room**

US 360 LiveLink

PRESENCE DETECTOR

EAN 4007841008444

Illustrations

MOUNTING HEIGHT

2,5 – 3,5 m BEREICH	2,8 m OPTIMAL

US 360 LiveLink

PRESENCE DETECTOR

EAN **4007841008444**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841000363	**Aufputz-Adapter Control Pro IP54 weiss**	Accessory
	4007841003036	**Control PRO Schutzkorb**	Accessory
	4007841009151	**Smart Remote**	Accessory

ORDERING INFORMATION

Art.-Nr.	4007841008444
EAN	4007841008444
Typ	**US 360 LiveLink**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss