XLED home 2 Z-Wave graphite

SENSOR-SWITCHED LED FLOODLIGHT

EAN 4007841033996

- Including STEINEL LED system
- HCMC cooling system
- UV-resistant plastic
- Colour rendering index Ra =80

steinel

194 x 180 x 161 mm



XLED home 2 Z-Wave graphite

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841033996**

Technical Data

IDENTIFICATION

Variant	**graphite**

DIMENSIONS

Dimensions L × W × H	**194 x 180 x 161 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Power	**14,8 W**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
With motion detector	**Yes**
Detection angle	**140 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Tangential range	**r = 14 m (239 m²)**
Transmission range	**Up to 100 m in the open, 30 m indoors**

LIGHTING TECHNOLOGY

Colour temperature	**4000 K**
LED colour deviation	**SDCM3**
Colour rendering index	**80 - 89**
With illuminant	**Yes, STEINEL LED system**
Illuminant	**LED cannot be replaced**
LED cooling system	**HCMC (High Conductive Magnesium Composite)**
Luminous flux	**1184 lm**

LIFETIME

LED lifetime max. °C	**50000 h**
Luminous flux decline per LM80	**L70B10**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**8 s – 35 min**

HOUSING & MATERIAL

Impact resistance	**IK00**
Protection class (IP)	**IP44**
Protection class	**II**
Housing material	**HCMC**
Cover material	**Opal plastic**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

XLED home 2 Z-Wave graphite

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841033996**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841029876	**Smartfriends Box**	Accessory

ORDERING INFORMATION

Art.-Nr.	4007841033996
EAN	4007841033996
Typ	**XLED home 2 Z-Wave graphite**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss