# IS 3360 LiveLink - concealed installation, square

**MOTION DETECTOR**

EAN 4007841049379
E-Nr. 535955067

steinel

94 x 94 x 78 mm



# IS 3360 LiveLink - concealed installation, square

**MOTION DETECTOR**

EAN **4007841049379**
E-Nr. **535955067**

## Technical Data

### IDENTIFICATION

| | |
|---|---|
| Variant | **LiveLink - concealed installation, square** |
| Version | **Motion detectors** |
| Model | **LiveLink** |

### DIMENSIONS

| | |
|---|---|
| Dimensions L × W × H | **94 x 94 x 78 mm** |

### ELECTRICAL

| | |
|---|---|
| Mains connection | **230 V / 50 – 60 Hz** |
| Supply voltage detail | **DALI bus** |
| Livelink values | **Light level, Motion detection** |

### SENSOR TECHNOLOGY

| | |
|---|---|
| Sensor technology | **passive infrared** |
| Detection angle | **360 °** |
| Opening angle | **180 °** |
| Sneak-under protection | **Yes** |
| Segment-by-segment masking | **Yes** |
| Electronic scalability | **No** |
| Mechanical scalability | **No** |
| Radial range | **Ø 8 m (50 m²)** |
| Tangential range | **Ø 40 m (1257 m²)** |
| Switching zones | **1416 switching zones** |
| Mounting height | **2,5 – 4,0 m** |
| Presence range | **Ø 3 m (7 m²)** |
| Optimal mounting height | **2,8 m** |

### CONNECTIVITY

| | |
|---|---|
| Networking | **Yes** |
| Number of DALI participants | **3** |

### LIGHTING TECHNOLOGY

| | |
|---|---|
| Constant light regulation | **No** |

### SETTINGS

| | |
|---|---|
| Twilight setting | **2 – 1000 lx** |
| Time setting | **5 s – 15 min** |
| Base light function | **No** |
| Settings via | **LiveLink app** |
| With remote control | **No** |
| Twilight setting teach | **Yes** |

### HOUSING & MATERIAL

| | |
|---|---|
| Protection class (IP) | **IP20** |
| Ambient temperature | **-20...+50 °C** |
| Mounting location | **ceiling** |
| Application location | **Indoors, Outdoors** |
| Mounting type | **Concealed mounting** |
| Material | **Plastic** |
| Colour | **White** |
| RAL colour | **9003** |

### SCOPE OF DELIVERY & WARRANTY

| | |
|---|---|
| Manufacturer warranty | **5 years** |

### OTHER

| | |
|---|---|
| Application, location, room | **sports hall, side room, stairwell, wc, washroom, multi-storey car park, underground car park, warehouse, equipment room** |

# IS 3360 LiveLink - concealed installation, square

**MOTION DETECTOR**

EAN **4007841049379**
E-Nr. **535955067**

## Illustrations

**MOUNTING HEIGHT**

| | |
|---|---|
| 2,5 – 4,0 m<br>BEREICH | 2,8 m<br>OPTIMAL |

# IS 3360 LiveLink - concealed installation, square

**MOTION DETECTOR**

EAN **4007841049379**
E-Nr. **535955067**

## Accessories

### ORDERING INFORMATION

| | |
|---|---|
| Art.-Nr. | 4007841049379 |
| EAN | 4007841049379 |
| E-Number | 535955067 |
| Typ | **IS 3360 LiveLink - concealed installation, square** |

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss