IS 3180 LiveLink - surface-mounted, square

MOTION DETECTOR

EAN 4007841049409
E-Nr. 535941866

- UV-resistant plastic
- Optional corner wall mount bracket

steinel

95 x 95 x 65 mm



IS 3180 LiveLink - surface-mounted, square

MOTION DETECTOR

EAN **4007841049409**
E-Nr. **535941866**

Technical Data

IDENTIFICATION

Variant	**LiveLink - surface-mounted, square**
Version	**Motion detectors**
Model	**LiveLink**

DIMENSIONS

Dimensions L × W × H	**95 x 95 x 65 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Supply voltage detail	**DALI bus**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
Detection angle	**180 °**
Opening angle	**90 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**No**
Mechanical scalability	**No**
Tangential range	**r = 8 m (101 m²) / r = 20 m (628 m²)**
Switching zones	**448 switching zones**
Mounting height	**1,8 – 2,5 m**
Optimal mounting height	**2,0 m**

CONNECTIVITY

Networking	**Yes**
Number of DALI participants	**3**

LIGHTING TECHNOLOGY

Constant light regulation	**No**

SETTINGS

Twilight setting	**2 – 1000 lx**
Time setting	**5 s – 15 min**
Base light function	**No**
Settings via	**LiveLink app**
With remote control	**No**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP54**
Ambient temperature	**-20...+50 °C**
Mounting location	**corner, wall**
Application location	**Indoors, Outdoors**
Mounting type	**Surface mounting**
Material	**Plastic**
Colour	**White**
RAL colour	**9003**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

OTHER

Application, location, room	**corridor, aisle, stairwell, multi-storey car park, underground car park**

IS 3180 LiveLink - surface-mounted, square

MOTION DETECTOR

EAN **4007841049409**
E-Nr. **535941866**

Illustrations

MOUNTING HEIGHT

1,8 – 2,5 m BEREICH	2,0 m OPTIMAL

IS 3180 LiveLink - surface-mounted, square

MOTION DETECTOR

EAN **4007841049409**
E-Nr. **535941866**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841049409
EAN	4007841049409
E-Number	535941866
Typ	**IS 3180 LiveLink - surface-mounted, square**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss