IS 345 LiveLink - concealed installation, round

MOTION DETECTOR

EAN 4007841049447
E-Nr. 535955367

steinel

124 x 78 mm



IS 345 LiveLink - concealed installation, round

MOTION DETECTOR

EAN **4007841049447**
E-Nr. **535955367**

Technical Data

IDENTIFICATION

Variant	**LiveLink - concealed installation, round**
Version	**Motion detectors**
Model	**LiveLink**

DIMENSIONS

Dimensions Ø × H	**124 x 78 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Supply voltage detail	**DALI bus**
Livelink values	**Light level, Motion detection, Presence detection**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
Detection angle	**360 °**
Opening angle	**45 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**No**
Mechanical scalability	**No**
Radial range	**12 x 6 m (72 m²)**
Tangential range	**23 x 6 m (138 m²)**
Switching zones	**280 switching zones**
Mounting height	**2,5 – 5,0 m**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Number of DALI participants	**3**

LIGHTING TECHNOLOGY

Constant light regulation	**No**

SETTINGS

Twilight setting	**2 – 1000 lx**
Time setting	**5 s – 15 min**
Base light function	**No**
With remote control	**No**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**-20...+50 °C**
Mounting location	**ceiling**
Application location	**Indoors, Outdoors**
Mounting type	**Concealed mounting**
Material	**Plastic**
Colour	**White**
RAL colour	**9003**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

OTHER

Application, location, room	**corridor, aisle, underground car park, multi-storey car park**

IS 345 LiveLink - concealed installation, round

MOTION DETECTOR

EAN **4007841049447**
E-Nr. **535955367**

Illustrations

MOUNTING HEIGHT

2,5 – 5,0 m BEREICH	2,8 m OPTIMAL

IS 345 LiveLink - concealed installation, round

MOTION DETECTOR

EAN **4007841049447**
E-Nr. **535955367**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841049447
EAN	4007841049447
E-Number	535955367
Typ	**IS 345 LiveLink - concealed installation, round**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss