IS 3180 LiveLink - concealed installation, square

MOTION DETECTOR

EAN 4007841055752

- UV-resistant plastic

steinel

94 x 94 x 78 mm



IS 3180 LiveLink - concealed installation, square

MOTION DETECTOR

EAN 4007841055752

Technical Data

IDENTIFICATION

Variant	LiveLink - concealed installation, square
Version	Motion detectors

DIMENSIONS

Dimensions L × W × H	94 x 94 x 78 mm

ELECTRICAL

Mains connection	230 V / 50 – 60 Hz
Supply voltage detail	DALI bus

SENSOR TECHNOLOGY

Sensor technology	passive infrared
Detection angle	180 °
Opening angle	90 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No
Tangential range	r = 8 m (101 m²) / r = 20 m (628 m²)
Switching zones	448 switching zones
Mounting height	1,5 – 3,0 m
Optimal mounting height	2,0 m

CONNECTIVITY

Networking	Yes
Number of DALI participants	3

LIGHTING TECHNOLOGY

Constant light regulation	No

SETTINGS

Twilight setting	2 – 1000 lx
Time setting	5 s – 15 min
Base light function	Yes
Settings via	LiveLink app
With remote control	No
Twilight setting teach	No

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	-20…+50 °C
Mounting location	corner, wall
Application location	Indoors, Outdoors
Mounting type	Concealed mounting
Material	Plastic
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

OTHER

Application, location, room	corridor, aisle, stairwell, multi-storey car park, underground car park

IS 3180 LiveLink - concealed installation, square

EAN 4007841055752

MOTION DETECTOR

Illustrations

MOUNTING HEIGHT

1,5 – 3,0 m BEREICH	2,0 m OPTIMAL

IS 3180 LiveLink - concealed installation, square

EAN 4007841055752

MOTION DETECTOR

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841055752
EAN	4007841055752
Typ	**IS 3180 LiveLink - concealed installation, square**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss