# L 920 LED Silver

**SENSOR-SWITCHED OUTDOOR LIGHT**

EAN 4007841056490
E-Nr. 941200139

- Intelligent soft light start
- Interconnectable by cable
- 4-hour manual override (optional)
- High-quality aluminium
- Setting options protected from the weather and from outside influences

steinel

225 x 95 x 94 mm



# L 920 LED Silver

**SENSOR-SWITCHED OUTDOOR LIGHT**

EAN **4007841056490**
E-Nr. **941200139**

# Technical Data

### IDENTIFICATION

| | |
|---|---|
| Variant | **Silver** |

### DIMENSIONS

| | |
|---|---|
| Dimensions L × W × H | **225 x 95 x 94 mm** |

### ELECTRICAL

| | |
|---|---|
| Mains connection | **230 V / 50 – 60 Hz** |
| Power | **10 W** |

### SENSOR TECHNOLOGY

| | |
|---|---|
| Max. mounting height | **2,50 m** |
| Sensor technology | **passive infrared** |
| With motion detector | **Yes** |
| Detection angle | **140 °** |
| Sneak-under protection | **No** |
| Segment-by-segment masking | **No** |
| Electronic scalability | **Yes** |
| Mechanical scalability | **No** |
| Radial range | **r = 2 m (5 m²) / r = 4 m (20 m²)** |
| Tangential range | **r = 5 m (31 m²) / r = 12 m (176 m²)** |

### CONNECTIVITY

| | |
|---|---|
| Networking | **Yes** |

### LIGHTING TECHNOLOGY

| | |
|---|---|
| Colour temperature | **3000 K** |
| Colour rendering index | **80 - 89** |
| With illuminant | **Yes, STEINEL LED system** |
| Illuminant | **LED cannot be replaced** |
| Base | **without** |
| LED cooling system | **Passive Thermo Control** |
| Soft light start | **Yes** |
| Continuous light | **selectable, 4h** |
| Luminous flux | **571 lm** |

### LIFETIME

| | |
|---|---|
| LED lifetime max. °C | **50000 h** |

### SETTINGS

| | |
|---|---|
| Twilight switch | **Yes** |
| Twilight setting | **2 – 20 lx** |
| Time setting | **120 s – 15 min** |
| Base light function | **Yes** |
| Base light function time | **10-30 min, all night** |
| With remote control | **No** |

### HOUSING & MATERIAL

| | |
|---|---|
| Impact resistance | **IK00** |
| Protection class (IP) | **IP44** |
| Protection class | **II** |
| Ambient temperature | **-20...+40 °C** |
| Housing material | **Aluminium** |
| Cover material | **Opal plastic** |

### SCOPE OF DELIVERY & WARRANTY

| | |
|---|---|
| Manufacturer warranty | **3 years** |

# L 920 LED Silver

**SENSOR-SWITCHED OUTDOOR LIGHT**

EAN **4007841056490**
E-Nr. **941200139**

## Illustrations

**MOUNTING HEIGHT**

2,50 m
MAX

# L 920 LED Silver

**SENSOR-SWITCHED OUTDOOR LIGHT**

EAN **4007841056490**
E-Nr. **941200139**

## Accessories

**ORDERING INFORMATION**

| | |
|---|---|
| Art.-Nr. | 4007841056490 |
| EAN | 4007841056490 |
| E-Number | 941200139 |
| Typ | **L 920 LED Silver** |

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss