aluna connect LS P910 3K

PENDANT LUMINAIRE CONNECT

Product code **222038**

- Timeless simple textile lamp in 3 different sizes
- Available in ceiling and pendant versions
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- For universal use for illumination of offices, schools, traffic zones, etc.
- Very high quality workmanship from Swiss manufacturing
- Sophisticated thermal management for long service life
- Variants with adjustable light color (Tunable White) to emulate the natural course of daylight
- Fabric shade can be ordered in any color

910 x 118 mm



aluna connect LS P910 3K

PENDANT LUMINAIRE CONNECT

Product code **222038**

Technical Data

DIMENSIONS

Dimensions Ø × H	**910 x 118 mm**
Suspension length	**2000 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Power	**78 W**
Replaceable driver	**Yes**
Type of wiring	**Suitable for through wiring**

SENSOR TECHNOLOGY

With motion detector	**No**
With light sensor	**Yes**

CONNECTIVITY

With radio network control	**Yes**
Control technology	**Smartlink Connect**
Wireless networking via	**BT SIG Mesh**

LIGHTING TECHNOLOGY

Colour temperature	**3000 K**
LED colour deviation	**SDCM3**
Colour rendering index	**80 - 89**
Illuminant	**LED**
Luminous flux	**9800 lm (Down 8430, Up 1370)**
Beam angle	**105°**
Luminaire luminous efficacy	**126 lm/W**
Glare value	**UGR < 21**

LIFETIME

LED lifespan (25 °C)	**70000 h**

SETTINGS

DALI dimming	**Yes**
With emergency light	**No**
Direct/indirect ratio separately controllable	**No**
With program-controlled lighting control	**Yes**
Constant light output control	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Protection class	**I**
Ambient temperature	**-20...+45 °C**
Housing material	**Steel**
Cover material	**Acrylic glass opal**
Mounting type	**Pendant mounting**
Colour	**White**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

CERTIFICATES & EPREL

EPREL energy efficiency class	**D**


aluna connect LS P910 3K

PENDANT LUMINAIRE CONNECT

Product code **222038**

Illustrations

TECHNICAL DRAWINGS



910 x 118 mm


aluna connect LS P910 3K

PENDANT LUMINAIRE CONNECT

Product code **222038**


Wiring Diagrams

WIRING DIAGRAM 1



Wiring diagram networking radio

WIRING DIAGRAM 2



Wiring diagram pushbutton coupler

aluna connect LS P910 3K

PENDANT LUMINAIRE CONNECT

Product code **222038**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	221105	**ayana Diffusor 850 CDP**	Microprismatic Diffuser Ø850mm
	221108	**Emergency Package 1h (Astra)**	Self-contained emergency lighting with self-test function
	221366	**Connect RTC**	Real-time clock
	221570	**Connect TK2 BLM**	Pushbutton interface 2gang
	221846	**aluna Color RAL_NCS_Ø910**	Special color fabric shade Ø 0.91m
	221591	**Smartlink T-Board PB4**	Mobile push-button board
	221970	**Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2**	Wireless push-button, battery-free
	221971	**Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4**	Wireless push-button, battery-free

ORDERING INFORMATION

Art.-Nr.	222038
Typ	**aluna connect LS P910 3K**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss