Multisensor True Presence IP - concealed

MULTISENSOR

EAN 4007841081867
E-Nr. 535900071

- In our product portfolio of presence detectors with the most detection sizes
- Focus application: school, office
- Easy-to-install plug-in system with magnetic connection, integrated RBG LED traffic light and signal tone for visualising the room climate
- Digitally adjustable detection of true presence in award-winning design
- Measurement of brightness, temperature, humidity, CO2, VOC, air pressure, noise level
- Interface-dependent additional calculated values such as infection risk

steinel

123 x 123 x 53 mm



Multisensor True Presence IP - concealed

MULTISENSOR

EAN 4007841081867
E-Nr. 535900071

Technical Data

IDENTIFICATION

Variant	IP (REST API, MQTT, BacNet)
Version	Presence detector

DIMENSIONS

Dimensions L × W × H	123 x 123 x 53 mm

ELECTRICAL

Own consumption	1 W
Supply voltage detail	Passive PoE SELV, standard PoE (IEEE 802.3 af)

SENSOR TECHNOLOGY

Max. mounting height	12,00 m
Sensor technology	High frequency
Transmission power	< 10 mW
HF technology	7,2 GHz
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	160 °
Sneak-under protection	Yes
Segment-by-segment masking	No
Electronic scalability	Yes
Mechanical scalability	No
Radial range	Ø 15 m (177 m²)
Tangential range	Ø 15 m (177 m²)
Mounting height	2,0 – 12,0 m
Presence range	Ø 15 m (177 m²)
True Presence range	Ø 9 m (64 m²)
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
With bus coupler	Yes
Control technology	Steinel Connect
Wireless networking via	BT Open Mesh
Networking via	IP / IT

LIGHTING TECHNOLOGY

Continuous light	selectable

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Main light adjustable	Yes
Functions	Motions sensor, Light sensor
Settings via	Bluetooth Mesh, Web-Interface
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	0...+50 °C
Housing material	Plastic
Mounting location	ceiling
Application location	Indoors
Mounting type	Concealed mounting
Material	Plastic
Application room	classroom, conference room / meeting room, hotel room, open-plan office
Colour	White
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No


Multisensor True Presence IP - concealed

MULTISENSOR

EAN 4007841081867
E-Nr. 535900071

Illustrations

TECHNICAL DRAWINGS



123 x 123 x 53 mm

MOUNTING HEIGHT

2,0 – 12,0 m	2,8 m	12,00 m
BEREICH	OPTIMAL	MAX


Multisensor True Presence IP - concealed

MULTISENSOR

EAN 4007841081867
E-Nr. 535900071

Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

Multisensor True Presence IP - concealed

MULTISENSOR

EAN 4007841081867
E-Nr. 535900071


Highlights



UV-resistant plastic



Interconnectable and adjustable via Bluetooth



Digital high frequency sensor



Visual and auditory signal on room climate

Multisensor True Presence IP - concealed

MULTISENSOR

EAN 4007841081867
E-Nr. 535900071

Accessories

ORDERING INFORMATION

Art.-Nr.	081867
EAN	4007841081867
E-Number	535900071
Typ	**Multisensor True Presence IP - concealed**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss