RS PRO 5550 SC with motion detector - 4000K, emergency light

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841086879
E-Nr. 941463309

- Linear luminaire, 1500 mm, with integrated digital high-frequency sensor
- Ideal for passageways and office environments
- Easy conversion thanks to sliding bracket
- 5-core cable, through-wired and can be inserted from both sides or from the rear
- 360° motion detection with ø8 m range
- Precise adjustment of range and sensitivity
- Dimmable basic and main light from 10-100%
- All settings and networking easily via the free Steinel Connect app
- Suitable for connection to a central battery or as a single battery light with 3 hours of light

steinel

1500 x 164 x 75 mm



RS PRO 5550 SC with motion detector - 4000K, emergency light

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841086879
E-Nr. 941463309

Technical Data

IDENTIFICATION

Variant	Emergency light

DIMENSIONS

Dimensions L × W × H	1500 x 164 x 75 mm

ELECTRICAL

Mains connection	230 V / 50 – 60 Hz
Power	42 W

SENSOR TECHNOLOGY

Max. mounting height	3,50 m
Sensor technology	High frequency
HF technology	24 GHz
With motion detector	Yes
Detection angle	360 °
Opening angle	160 °
Segment-by-segment masking	No
Electronic scalability	Yes
Mechanical scalability	No
Radial range	Ø 8 m (50 m²)
Tangential range	Ø 8 m (50 m²)
Mounting height	2,0 – 3,5 m
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Type of networking	Master/Master
Slave mode adjustable	Yes
Control technology	Steinel Connect
Wireless networking via	BT SIG Mesh
Networking via	Bluetooth Mesh

LIGHTING TECHNOLOGY

Colour temperature	4000 K
LED colour deviation	SDCM3
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	Other
LED cooling system	Passive Thermo Control
Soft light start	Yes
Continuous light	selectable
Luminous flux emergency light	730 lm

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 min
Base light function	Yes
Base light function time	1-60 min
Main light adjustable	10 - 100 %
Functions	DIM function, Orientation light, Light sensor, Connection to central battery systems, Motions sensor, Adjustable fade time when switching on and off, Free selection of the light value in a luminaire group, Group parameterisation, Neighbouring group function, Encrypted communication, Emergency light in compliance with EN 60598-2-22 for 3h
Settings via	App, Smartphone, Tablet, Bluetooth
With remote control	No
Twilight setting teach	Yes
Base light function in percent	10 – 100 %
Base light function percent from	10 %

HOUSING & MATERIAL

Impact resistance	IK07
Protection class (IP)	IP44
Protection class	II
Ambient temperature	-20...+40 °C
Housing material	Plastic
Cover material	Opal plastic
Mounting location	ceiling, wall
Application location	Indoors
Mounting type	Surface mounting
Application room	Indoors, WC / washroom, changing room, corridor / aisle, function room / ancillary room, multi-storey / underground car park, stairwell, warehouse
Colour	White

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
House number sheet included	No

CERTIFICATES & EPREL

EPREL category	Surrounded product with integrated light source


RS PRO 5550 SC with motion detector - 4000K, emergency light

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841086879**
E-Nr. **941463309**

Illustrations

TECHNICAL DRAWINGS



1500 x 164 x 75 mm

MOUNTING HEIGHT

2,0 – 3,5 m	2,8 m	3,50 m
BEREICH	OPTIMAL	MAX


RS PRO 5550 SC with motion detector - 4000K, emergency light

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841086879**
E-Nr. **941463309**

Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

RS PRO 5550 SC with motion detector - 4000K, emergency light

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841086879**
E-Nr. **941463309**

Accessories

ORDERING INFORMATION

Art.-Nr.	086879
EAN	4007841086879
E-Number	941463309

Typ**RS PRO 5550 SC with motion detector - 4000K, emergency light**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss