

iFux CityStreet3 Connect DN10 3K Master



IFUX CITYSTREET 3 CONNECT

Product code **220662**

- Intelligent pole-mounted luminaire for inspiring outdoor lighting solutions
- Built-in lighting control including motion detection, orientation light and neighbor function
- Wireless networking by radio
- High-quality, noble processing with glare-free illumination
- Designed for the lighting of urban, street and pedestrian areas
- Option cloud maintenance and lighting control platform via gateway or GPS Version

neva
lux

520 x 300 x 130 mm



iFux CityStreet3 Connect DN10 3K Master

IFUX CITYSTREET 3 CONNECT

Product code 220662

Technical Data

IDENTIFICATION		CONNECTIVITY		HOUSING & MATERIAL	
Variant	Narrow beam DN10	With radio network control	Yes	Impact resistance	IK09
DIMENSIONS		LIGHTING TECHNOLOGY		Protection class (IP)	IP66
Dimensions L x W x H	520 x 300 x 130 mm	Colour temperature	3000 K	Protection class	II
Suitable for pole-top diameter	48...76 mm	Colour rendering index	70-79	Ambient temperature	-30...55 °C
ELECTRICAL		With illuminant	Yes, LED-System	Housing material	Aluminium
Mains connection	90...264 VAC / 47 – 63 Hz	Luminous flux	8520 lm	Cover material	Clear glass
Power	60 W	Beam angle	Narrow	Mounting type	Column side-entry
Power factor	0.92	Luminaire luminous efficacy	142 lm/W	Colour	Anthracite
SENSOR TECHNOLOGY		LIFETIME		SCOPE OF DELIVERY & WARRANTY	
Sensor technology	passive infrared	LED lifespan (25 °C)	100000 h	Manufacturer warranty	5 years
With motion detector	Yes	SETTINGS		With connection cable	Yes
Detection angle	100 °	DALI dimming	Yes	CERTIFICATES & EPREL	
Tangential range	10 m	With program-controlled lighting control	Yes	EPREL energy efficiency class	A++, A+, A (LED)
With light sensor	Yes				

iFux CityStreet3 Connect DN10 3K Master

Product code 220662

IFUX CITYSTREET 3 CONNECT

Accessories

ORDERING INFORMATION	
Art.-Nr.	220662
Typ	iFux CityStreet3 Connect DN10 3K Master
neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	