

XLED PRO ONE ohne Bewegungsmelder - anthrazit

neva
lux

XLED PRO ONE

Product code **4007841069513**

E-Nr. **941502119**

- High-quality aluminium
- Panel can be moved to the top or bottom
- UV resistant material
- Optional surface-mounting adapter

neva
lux

182 x 229 x 206 mm



XLED PRO ONE ohne Bewegungsmelder - anthrazit

Product code 4007841069513
E-Nr. 941502119

XLED PRO ONE

Technical Data

DIMENSIONS		With illuminant	Yes, STEINEL LED system	Ambient temperature	-20 – 40 °C
Dimensions L x W x H	182 x 229 x 206 mm	Illuminant	LED cannot be replaced	Housing material	Aluminium
ELECTRICAL		Base	without	Cover material	Glass transparent
Mains connection	220 – 240 V / 50 – 60 Hz	LED cooling system	Passive Thermo Control	Cover material (scope of delivery)	shrouds
Power	17,7 W	LIFETIME		Mounting location	ceiling wall
SENSOR TECHNOLOGY		LED lifetime L70B50 25°C	> 36000 h	Application location	Outdoors
With motion detector	No	SETTINGS		Mounting type	Surface wiring
CONNECTIVITY		Twilight switch	No	Application room	all round the building courtyard & driveway front door garden outdoors
Networking	Yes	Base light function	No	Colour	Anthracite
Type of networking	Master/slave	Main light adjustable	No	SCOPE OF DELIVERY & WARRANTY	
Networking via	Cable	Functions	Relay output	Manufacturer warranty	5 years
LIGHTING TECHNOLOGY		Twilight setting teach	No	Corner wall bracket included	No
Measured luminous flux 360°	2236 lm	HOUSING & MATERIAL		CERTIFICATES & EPREL	
Colour temperature	3000 K	Impact resistance	IK03	EPREL category	Light source
LED colour deviation	SDCM3	Protection class (IP)	IP44		
Colour rendering index	80-89	Protection class	I		

XLED PRO ONE ohne Bewegungsmelder - anthrazit

Product code **4007841069513**
E-Nr. **941502119**

XLED PRO ONE

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841080990	Aufputz-Adapter XLED PRO ONE anthrazit	Adapter
 4007841079000	RC 12	Other

ORDERING INFORMATION

Art.-Nr.

4007841069513

E-Number

941502119

Typ

XLED PRO ONE ohne Bewegungsmelder - anthrazit

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss