RS PRO LED R1 Neutral white white

SENSOR-SWITCHED INDOOR LIGHT

EAN 4007841033354

- Including STEINEL LED system
- Optional basic lighting level 20 %
- Intelligent soft light start
- Interconnectable by cable

270 x 70 mm



RS PRO LED R1 Neutral white white

SENSOR-SWITCHED INDOOR LIGHT

EAN 4007841033354

Technical Data

IDENTIFICATION

Variant	Neutral white white

DIMENSIONS

Dimensions Ø × H	270 x 70 mm

ELECTRICAL

Mains connection	220 – 240 V , 50 / 60 Hz
Power	11 W
Switching output 1 resistive	800 W

SENSOR TECHNOLOGY

Sensor technology	High frequency
Transmission power	< 1 mW
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	160 °
Electronic scalability	Yes
Mechanical scalability	No

CONNECTIVITY

Networking	Yes
Type of networking	Sensor/slave
Networking quantity	10 lights max.
Control technology	On/Off-Leuchte

LIGHTING TECHNOLOGY

Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Continuous light	selectable, 4h
Luminous flux	950 lm

LIFETIME

LED lifetime max. °C	50000 h
Luminous flux decline per LM80	L70B10

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 sec – 15 min

HOUSING & MATERIAL

Impact resistance	IK00
Protection class (IP)	IP20
Protection class	II
Ambient temperature	-10 – 50 °C
Housing material	Plastic
Cover material	Plastic, opal

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

RS PRO LED R1 Neutral white white

SENSOR-SWITCHED INDOOR LIGHT

EAN **4007841033354**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841033354
EAN	4007841033354
Typ	**RS PRO LED R1 Neutral white white**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss