

nefera S V2 Connect CCT

NEFERA CONNECT S

neva
lux

Product code **222043**

- For the perfect illumination of one workplace
- Flat design and absolutely homogeneous illumination
- Available as intelligent Connect or as simple sensor variant
- Connect variant with powerful IoT lighting control for next-generation lighting projects (swarm function, grouping, cleaning light, etc.)
- Direct and indirect light distribution
- Very good glare control values (UGR < 18)
- Optionally in a color temperature of 4000K or with manually adjustable color temperature from 3000K to 5700K (CCT)
- High quality finish
- Housing aluminum white

neva
lux

726 x 310 x 1954 mm



nefera S V2 Connect CCT

NEFERA CONNECT S

Product code 222943

Technical Data

DIMENSIONS		LIGHTING TECHNOLOGY		With program-controlled lighting control		Yes
Dimensions L x W x H	726 x 310 x 1954 mm	Colour temperature	3000...5700 K	Constant light output control		Yes
ELECTRICAL		LED colour deviation	SDCM3	With switch		Yes
Mains connection	200...240 V / 50 – 60 Hz	Colour rendering index	80-89	HOUSING & MATERIAL		
Power	80 W	Illuminant	LED	Protection class (IP)		IP20
Replaceable driver	Yes	Luminous flux	10400 lm (Down 3850, Up 6550)	Protection class		I
SENSOR TECHNOLOGY		Beam angle	Down 80°, Up 115°	Ambient temperature		-20...45 °C
Sensor technology	passive infrared	Luminaire luminous efficacy	130 lm/W	Housing material		Aluminum
With motion detector	Yes	Glare value	UGR < 18	Cover material		Microprismatic acrylic glass
Detection angle	360 °	LIFETIME		Mounting type		Free standing floor
Radial range	4 x 4 m (16 m²)	LED lifespan (25 °C)	50000 h	Colour		white
Tangential range	4 x 4 m (16 m²)	SETTINGS		SCOPE OF DELIVERY & WARRANTY		
Presence range	4 x 4 m (16 m²)	DALI dimming	Yes	Manufacturer warranty		5 years
With light sensor	Yes	Direct/indirect ratio separately controllable	No	CERTIFICATES & EPREL		
CONNECTIVITY				EPREL energy efficiency class		D
With radio network control	Yes					

nefera S V2 Connect CCT

NEFERA CONNECT S

Product code 222043

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221570	Connect TK2 BLM	Pushbutton interface

ORDERING INFORMATION

Art.-Nr.

222043

Typ

nefera S V2 Connect CCT

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss