RS PRO LED S1 Glass Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841057787
E-Nr. 941000079

- Including STEINEL LED system
- Intelligent LED cooling system
- Optional basic lighting level 10 %
- Wireless interconnection
- High-quality aluminium
- Optional remote control

300 x 86 mm



RS PRO LED S1 Glass Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841057787**
E-Nr. **941000079**

Technical Data

IDENTIFICATION

Variant	**Glass Neutral white**

DIMENSIONS

Dimensions Ø × H	**300 x 86 mm**

ELECTRICAL

Mains connection	**230 – 240 V / 50 – 60 Hz**
Power	**15 W**
Own consumption	**0,5 W**

SENSOR TECHNOLOGY

Sensor technology	**High frequency**
Transmission power	**< 1 mW**
HF technology	**5,8 GHz**
With motion detector	**Yes**
Detection	**also through glass, wood and stud walls**
Detection angle	**360 °**
Opening angle	**160 °**
Segment-by-segment masking	**No**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Radial range	**Ø 8 m (50 m²)**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/master, Master/slave**
Slave mode adjustable	**Yes**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Colour temperature	**4000 K**
LED colour deviation	**SDCM3**
Colour rendering index	**80-89**
With illuminant	**Yes, STEINEL LED system**
Illuminant	**LED cannot be replaced**
Base	**without**
LED cooling system	**Active Thermo Control**
Soft light start	**Yes**
Continuous light	**selectable, 4h**
Luminous flux	**1092 lm**

LIFETIME

LED lifetime max. °C	**70000 h**
Luminous flux decline per LM80	**L80B10**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**5 sec – 15 min**
Base light function	**Yes**
Base light function time	**10/30 min, all night**
Functions	**Neighbouring-group function, Presence function, Group parameterisation, Manual ON / ON-OFF**
Settings via	**DIP switches, Potentiometers, Remote control, Smart Remote**
With remote control	**No**

HOUSING & MATERIAL

Impact resistance	**IK03**
Protection class (IP)	**IP20**
Protection class	**II**
Ambient temperature	**-10 – 50 °C**
Housing material	**Aluminium**
Cover material	**Glass opal**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**


RS PRO LED S1 Glass Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841057787**
E-Nr. **941000079**

Illustrations

TECHNICAL DRAWINGS



300 x 86 mm


RS PRO LED S1 Glass Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841057787**
E-Nr. **941000079**


Wiring Diagrams

WIRING DIAGRAM 1



Slave/wireless master interconnection circuit diagram

WIRING DIAGRAM 2



Master/master interconnection circuit diagram

RS PRO LED S1 Glass Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841057787**
E-Nr. **941000079**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841009151	**Smart Remote**	Accessory

ORDERING INFORMATION

Art.-Nr.	4007841057787
EAN	4007841057787
E-Number	941000079
Typ	**RS PRO LED S1 Glass Neutral white**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss