

US 360 DIM

neva
lux

Product code **4007841007959**

- Optional remote controls
- Optional surface-mounting adapter
- Optional guard cage

neva
lux

120 x 120 x 68 mm



US 360 DIM

Product code **4007841007959**

Technical Data

IDENTIFICATION				HOUSING & MATERIAL	
Variant	DIM	Tangential range	Ø 10 m (79 m²)	Protection class (IP)	IP20
Version	Presence detector	Mounting height	2,50 – 3,50 m	Ambient temperature	-25 – 55 °C
DIMENSIONS		Presence range	Ø 6 m (28 m²)	Mounting location	ceiling
Dimensions L x W x H	120 x 120 x 68 mm	Optimal mounting height	2,8 m	Application location	Indoors
ELECTRICAL		CONNECTIVITY		Mounting type	Concealed wiring
Mains connection	230 V, 50 / 60 Hz	Networking	Yes	Material	Plastic
Number of ECGs DIM interface	50	Type of networking	Master/slave, Master/master	Colour	white
SENSOR TECHNOLOGY		LIGHTING TECHNOLOGY		RAL colour	9010
Sensor technology	Ultrasonic	Constant light regulation	Yes	SCOPE OF DELIVERY & WARRANTY	
Detection angle	360 °	SETTINGS		Manufacturer warranty	5 years
Sneak-under protection	Yes	Twilight setting	100 – 1000 lx	OTHER	
Electronic scalability	Yes	Time setting	30 sec – 30 min	Application, location, room	classroom, One-person office, Open-plan office, conference room, side room, stairwell, washroom, wc, equipment room
Mechanical scalability	No	Base light function	Yes		
Radial range	Ø 10 m (79 m²)	With remote control	No		
		Twilight setting teach	Yes		

US 360 DIM

Product code **4007841007959**

Illustrations

MOUNTING HEIGHT

2,50 – 3,50 m BEREICH	2,8 m OPTIMAL
---	-------------------------------------

US 360 DIM

Product code 4007841007959

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841592806	Nutzer Fernbedienung RC5	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841007959

Typ

US 360 DIM

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss