elani P1500 4K

PENDANT LUMINAIRE

Product code **221124**

- For universal use for lighting offices, schools, traffic zones etc.
- Direct and indirect light can be controlled separately
- Dimmable DALI
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

1500 x 60 x 80 mm



elani P1500 4K

PENDANT LUMINAIRE

Product code **221124**

Technical Data

DIMENSIONS

Dimensions L × W × H	**1500 x 60 x 80 mm**
Suspension length	**2000 mm**

ELECTRICAL

Mains connection	**200…240 V / 50 – 60 Hz**
Power	**47 W**
Replaceable driver	**Yes**
Type of wiring	**Suitable for through wiring**

SENSOR TECHNOLOGY

With motion detector	**Yes**
With light sensor	**No**

CONNECTIVITY

Control technology	**Dali-Leuchte**
Networking via	**DALI 2**

LIGHTING TECHNOLOGY

Colour temperature	**4000 K**
LED colour deviation	**SDCM3**
Colour rendering index	**80-89**
Illuminant	**Yes, LED-System**
Beam angle	**Down 105°, Up 115°**
Luminaire luminous efficacy	**128 lm/W**
Glare value	**UGR < 22**

LIFETIME

LED lifespan (25 °C)	**70000 h**

SETTINGS

DALI dimming	**Yes**
With emergency light	**No**
Suitable for light band configuration	**Yes**
Direct/indirect ratio separately controllable	**Yes**
Constant light output control	**No**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Protection class	**II**
Ambient temperature	**-20…45 °C**
Housing material	**Aluminium**
Cover material	**Acrylic glass opal**
Mounting type	**Ceiling pendant**
Colour	**Aluminium**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

CERTIFICATES & EPREL

EPREL energy efficiency class	**D**


elani P1500 4K

PENDANT LUMINAIRE

Product code **221124**

Illustrations

TECHNICAL DRAWINGS



1500 x 60 x 80 mm


elani P1500 4K

PENDANT LUMINAIRE

Product code **221124**


Wiring Diagrams

WIRING DIAGRAM 1



Wiring diagram

WIRING DIAGRAM 2



Wiring diagram

elani P1500 4K

PENDANT LUMINAIRE

Product code **221124**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	221100	**elani Diffusor 1500 CDP**	Microprismatic Diffuser 1500mm
	221343	**elani Connector 90°**	90° connection with miter cut
	221107	**elani Link**	Connection of luminaires
	221106	**elani Color RAL_NCS_1500**	Special paint 1.5m
	221996	**elani WM-Set 2B**	Wall mounting kit

ORDERING INFORMATION

Art.-Nr.	221124
Typ	**elani P1500 4K**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss