

elani P3200 3K

ELANI

neva
lux

Product code **221121**

- For universal use for lighting offices, schools, traffic zones etc.
- Direct and indirect light can be controlled separately
- Dimmable DALI
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

neva
lux

3140 x 60 x 80 mm



elani P3200 3K

ELANI

Product code 221121

Technical Data

DIMENSIONS					
Dimensions L x W x H	3140 x 60 x 80 mm	Colour rendering index	80-89	Constant light output control	No
Suspension length	2000 mm	Illuminant	Yes, LED-System	HOUSING & MATERIAL	
ELECTRICAL		Beam angle	Down 105°, Up 115°	Protection class (IP)	IP20
Mains connection	200...240 V / 50 – 60 Hz	Luminaire luminous efficacy	129 lm/W	Protection class	II
Power	97 W	Glare value	UGR < 22	Ambient temperature	-20...45 °C
Replaceable driver	Yes	LIFETIME		Housing material	Aluminium
Type of wiring	Suitable for through wiring	LED lifespan (25 °C)	70000 h	Cover material	Acrylic glass opal
SENSOR TECHNOLOGY		SETTINGS		Mounting type	Ceiling pendant
With motion detector	Yes	DALI dimming	Yes	Colour	Aluminium
With light sensor	No	With emergency light	No	SCOPE OF DELIVERY & WARRANTY	
LIGHTING TECHNOLOGY		Suitable for light band configuration	Yes	Manufacturer warranty	5 years
Colour temperature	3000 K	Direct/indirect ratio separately controllable	Yes	CERTIFICATES & EPREL	
LED colour deviation	SDCM3			EPREL energy efficiency class	D

elani P3200 3K

ELANI

Product code 221121

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221102	elani Diffusor 3200 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221343	elani Connector 90°	Coupler/connector L-shape
 221107	elani Link	Coupler/connector straight
 221397	elani Color RAL_NCS_3200	Other
 221997	elani WM-Set 3B	Mounting kit

ORDERING INFORMATION

Art.-Nr.221121

Typelani P3200 3K

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss