L 244 LED Stainless steel

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841033255

- Including STEINEL LED system
- LED ambient light
- Rustproof stainless steel trim
- Impact-resistant material rated to IK07

305 x 165 x 81 mm



L 244 LED Stainless steel

SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841033255**

Technical Data

IDENTIFICATION

Variant	**Stainless steel**

DIMENSIONS

Dimensions L × W × H	**305 x 165 x 81 mm**

ELECTRICAL

Mains connection	**220 – 240 V , 50 / 60 Hz**
Power	**7,5 W**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
With motion detector	**Yes**
Detection angle	**180 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**No**
Mechanical scalability	**No**
Radial range	**r = 3 m (14 m²)**
Tangential range	**r = 10 m (157 m²)**

CONNECTIVITY

Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Colour temperature	**3000 K**
LED colour deviation	**SDCM3**
Colour rendering index	**80-89**
With illuminant	**Yes, STEINEL LED system**
Illuminant	**LED cannot be replaced**
Base	**without**
LED cooling system	**Passive Thermo Control**
Luminous flux	**500 lm**

LIFETIME

LED lifetime max. °C	**50000 h**
Luminous flux decline per LM80	**L70B10**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**8 sec – 35 min**

HOUSING & MATERIAL

Impact resistance	**IK07**
Protection class (IP)	**IP44**
Protection class	**II**
Ambient temperature	**-20 – 50 °C**
Housing material	**Stainless steel**
Cover material	**Plastic, opal**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**3 years**

L 244 LED Stainless steel

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841033255

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841033255
EAN	4007841033255
Typ	**L 244 LED Stainless steel**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss