

Dual HF LiveLink



Product code **4007841009700**

E-Nr. **535930507**

- Optional surface-mounting adapter
- Optional guard cage
- HF ceiling adapter for installation in suspended ceilings
- Settings via LiveLink app

neva
lux

120 x 120 x 55 mm



Dual HF LiveLink

Product code **4007841009700**
E-Nr. **535930507**

Technical Data

IDENTIFICATION					
Variant	LiveLink	Electronic scalability	Yes	Settings via	LiveLink app
Version	Presence detector	Mechanical scalability	No	With remote control	No
Model	LiveLink	Radial range	20 x 3 m (60 m²)	Twilight setting teach	Yes
DIMENSIONS		Tangential range	20 x 3 m (60 m²)	HOUSING & MATERIAL	
Dimensions L x W x H	120 x 120 x 55 mm	Mounting height	2,50 – 3,50 m	Ambient temperature	-25 – 50 °C
ELECTRICAL		Optimal mounting height	2,8 m	Mounting location	ceiling
Mains connection	230 V, 50 / 60 Hz	CONNECTIVITY		Application location	Indoors
Livelink values	Light level, Motion detection	Number of DALI participants	8	Mounting type	Concealed wiring
SENSOR TECHNOLOGY		With bus coupler	Yes	Material	Plastic
Sensor technology	High frequency	LIGHTING TECHNOLOGY		Colour	white
HF technology	5,8 GHz	Constant light regulation	No	RAL colour	9010
Detection angle	360 °	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
Opening angle	140 °	Twilight setting	10 – 1000 lx	Manufacturer warranty	5 years
Sneak-under protection	Yes	Time setting	30 sec – 60 min	OTHER	
		Base light function	No	Application, location, room	corridor, aisle

Dual HF LiveLink

Product code **4007841009700**
E-Nr. **535930507**

Illustrations

MOUNTING HEIGHT

2,50 – 3,50 m BEREICH	2,8 m OPTIMAL
--------------------------	------------------

Dual HF LiveLink

Product code **4007841009700**
E-Nr. **535930507**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841000363	Aufputz-Adapter Control Pro IP54 weiss	Accessory
 4007841003036	Control PRO Schutzkorb	Accessory
 4007841006600	HF-Deckenadapter	Accessory
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841009700

E-Number

535930507

Typ

Dual HF LiveLink

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss