HF 360-2 KNX - Concealed wiring

PRESENCE DETECTOR

EAN 4007841064303
E-Nr. 535931508

steinel

60 x 103 x 103 mm



HF 360-2 KNX - Concealed wiring

PRESENCE DETECTOR

EAN **4007841064303**
E-Nr. **535931508**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**60 x 103 x 103 mm**

ELECTRICAL

Mains connection	**30 V**
Supply voltage detail	**KNX bus**

SENSOR TECHNOLOGY

Max. mounting height	**4,00 m**
Sensor technology	**High frequency**
Transmission power	**< 1 mW**
HF technology	**5,8 GHz**
With motion detector	**Yes**
Detection	**also through glass, wood and stud walls**
Detection angle	**360 °**
Opening angle	**140 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**Yes**
Mechanical scalability	**No**
Range detail	**1 or 2 detection directions can be masked out by stickers for adjustment to the room situation.**
Radial range	**Ø 12 m (113 m²)**
Tangential range	**Ø 12 m (113 m²)**
Mounting height	**2,50 – 4,00 m**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/master Master/slave**
KNX functions	**Comfort Photo-cell controller Individual pyro evaluation Basic light level function Light level HVAC output Constant-lighting control Light output 4x Humidity output Presence output Day / night function Dewpoint Temperature output Logic gate**
With bus coupler	**Yes**
Networking via	**KNX**

LIGHTING TECHNOLOGY

Soft light start	**Yes**
Continuous light	**selectable**
Constant light regulation	**Yes**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 1000 lx**
Time setting	**10 s – 1092 Min.**
Base light function	**Yes**
Main light adjustable	**0 - 100 %**
Settings via	**ETS software Bluetooth Bus**
With remote control	**No**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from -25 up to 50 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Concealed wiring**
Material	**Plastic**
Application room	**Indoors WC / washroom function room / ancillary room kitchenette stairwell**
Colour	**white**
RAL colour	**9003**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**


HF 360-2 KNX - Concealed wiring

PRESENCE DETECTOR

EAN **4007841064303**
E-Nr. **535931508**

Illustrations

TECHNICAL DRAWINGS



60 x 103 x 103 mm

MOUNTING HEIGHT

2,50 – 4,00 m	2,8 m	4,00 m
BEREICH	OPTIMAL	MAX

HF 360-2 KNX - Concealed wiring

PRESENCE DETECTOR

EAN **4007841064303**
E-Nr. **535931508**

Highlights



UV-resistant plastic

HF 360-2 KNX - Concealed wiring

PRESENCE DETECTOR

EAN **4007841064303**
E-Nr. **535931508**

Accessories

ORDERING INFORMATION

Art.-Nr.	064303
EAN	4007841064303
E-Number	535931508
Typ	**HF 360-2 KNX - Concealed wiring**

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss