

RS PRO DL LED 20 W neutralweiss

neva
lux

Product code **4007841007751**

E-Nr. **941313009**

- Including STEINEL LED system
- Intelligent LED cooling system
- Ceiling-flush installation
- Interconnectable by cable ?(maximum of 10 units)
- Can only be set by optional remote control RC2

neva
lux

168 x 88 mm



RS PRO DL LED 20 W neutralweiss

Product code **4007841007751**
E-Nr. **941313009**

Technical Data

IDENTIFICATION					
Variant	Neutral white	Opening angle	160 °	Luminous flux decline per LM80	L70B10
DIMENSIONS		Electronic scalability	Yes	SETTINGS	
Dimensions Ø × H	168 x 88 mm	Mechanical scalability	No	Twilight switch	Yes
ELECTRICAL		LIGHTING TECHNOLOGY		Time setting	60 sec – 60 min
Mains connection	100 – 240 V , 50 / 60 Hz	Colour temperature	4000 K	Base light function time	10 min, 30 min, all night
Power	20 W	LED colour deviation	SDCM3	HOUSING & MATERIAL	
Power detail	Only via Eltako ER12DX-UC	Colour rendering index	70-79	Impact resistance	IK00
SENSOR TECHNOLOGY		With illuminant	Yes, STEINEL LED system	Protection class (IP)	IP20
Sensor technology	High frequency	Illuminant	LED cannot be replaced	Protection class	II
Transmission power	< 1 mW	Base	without	Ambient temperature	-10 – 40 °C
With motion detector	Yes	LED cooling system	Passive Thermo Control	Housing material	Aluminium
Detection	also through glass, wood and stud walls	Luminous flux	1230 lm	Cover material	Plastic, opal
Detection angle	360 °	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
		LED lifetime max. °C	50000 h	Manufacturer warranty	5 years

RS PRO DL LED 20 W neutralweiss

Product code **4007841007751**
E-Nr. **941313009**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841737818	RS PRO Fernbedienung RC2	
 4007841009151	Smart Remote	Accessory
 4007841013684	Sanierungsblende für RS PRO DL LED 20 W	

ORDERING INFORMATION

Art.-Nr.

4007841007751

E-Number

941313009

Typ

RS PRO DL LED 20 W neutralweiss

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss