

L 626 LED Alu silber

neva
lux

Product code **4007841053154**

- Including STEINEL LED system
- Intelligent soft light start
- Optional basic lighting level 20 %
- Sensor with 4 intelligent programmes
- High-quality aluminium
- UV resistant material

neva
lux

122 x 269 x 102 mm



L 626 LED Alu silber

Product code 4007841053154

Technical Data

IDENTIFICATION					
Variant	aluminium silver	With motion detector	Yes	Soft light start	Yes
DIMENSIONS		Detection angle	360 °	Luminous flux	595 lm
Dimensions L x W x H	122 x 269 x 102 mm	Opening angle	90 °	SETTINGS	
ELECTRICAL		Sneak-under protection	Yes	Twilight setting	2 – 1000 lx
Mains connection	220 – 240 V , 50 / 60 Hz	Tangential range	r = 7 m (154 m²)	Time setting	5 sec – 15 min
SENSOR TECHNOLOGY		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Sensor technology	passive infrared	Efficiency	66 lm/W	Protection class (IP)	IP44
		Colour temperature	3000 K	Protection class	I
		LED colour deviation	SDCM3	Ambient temperature	-20 – 50 °C

L 626 LED Alu silber

Product code 4007841053154

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841006365	Ersatzglas für L 270 / L 625 / L 626	
 4007841009038	Ersatz-Minisensor silber	Spare Part

ORDERING INFORMATION

Art.-Nr.

4007841053154

Typ

L 626 LED Alu silber

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss