

RS PRO P2 flat S Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

neva
lux

EAN 4007841069735

E-Nr. 941003549

 **steinel**

322 x 68 mm



RS PRO P2 flat S Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841069735
E-Nr. 941003549

Technical Data

DIMENSIONS	
Dimensions Ø × H	322 x 68 mm
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	15,4 W
Switching output 1 low-voltage halogen lamps	800 VA
LED lamps > 8 W	250 W
Capacitive load in µF	88 µF
Switching output 1 number of LED/fluorescent lamps	50 pcs.
SENSOR TECHNOLOGY	
Max. mounting height	4,00 m
Sensor technology	High frequency
With motion detector	Yes
Detection angle	360 °
Electronic scalability	Yes
Mechanical scalability	No
Radial range	Ø 8 m (50 m²)
Tangential range	Ø 8 m (50 m²)
Mounting height	2 – 4 m
Optimal mounting height	2,8 m
CONNECTIVITY	
Networking	Yes
Networking via	Cable
LIGHTING TECHNOLOGY	
Measured luminous flux 360°	1700 lm
Colour temperature	4000 K
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
LIFETIME	
LED lifetime max. °C	50000 h
LED lifetime L70B50 25°C	> 60000 h
Luminous flux decline per LM80	L80B10
SETTINGS	
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 Min.
Base light function	Yes
Base light function time	10/30 min, all night
Main light adjustable	No
Base light function in percent	10 %
Base light function percent from	10 %
HOUSING & MATERIAL	
Impact resistance	IK03
Protection class (IP)	IP54
Protection class	II
Ambient temperature	from -10 up to 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Mounting location	ceiling wall
Colour	white
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
Certificates	DEKRA
EPREL category	Surrounded product with integrated light source


RS PRO P2 flat S Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841069735
E-Nr. 941003549

Illustrations

TECHNICAL DRAWINGS



322 x 68 mm

MOUNTING HEIGHT

2 – 4 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
--------------------	------------------	---------------

RS PRO P2 flat S Neutral white


SENSOR-SWITCHED LED INDOOR LIGHT

EAN 4007841069735

E-Nr. 941003549


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/master interconnection circuit diagram

RS PRO P2 flat S Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT


EAN 4007841069735

E-Nr. 941003549

Highlights



Including STEINEL LED system



Intelligent soft light start



Interconnectable by cable (maximum of 10 units)



Optional basic lighting level 10 %

RS PRO P2 flat S Neutral white

SENSOR-SWITCHED LED INDOOR LIGHT

EAN **4007841069735**

E-Nr. **941003549**

Accessories

ORDERING INFORMATION	
Art.-Nr.	069735
EAN	4007841069735
E-Number	941003549
Typ	RS PRO P2 flat S Neutral white
neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	