XLED curved S white

SENSOR-SWITCHED LED FLOODLIGHT

EAN 4007841012083
E-Nr. 941200269

- Including STEINEL LED system
- HCMC cooling system
- UV-resistant plastic
- Colour rendering index Ra ≥ 80

120 x 160 x 107 mm



XLED curved S white

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841012083**
E-Nr. **941200269**

Technical Data

DIMENSIONS

Dimensions L × W × H	**120 x 160 x 107 mm**

ELECTRICAL

Mains connection	**220 – 240 V / 50 – 60 Hz**
Power	**9,3 W**
Own consumption	**0,5 W**

SENSOR TECHNOLOGY

Max. mounting height	**4,00 m**
Sensor technology	**Passiv Infrarot**
With motion detector	**Yes**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**No**
Mechanical scalability	**No**
Mounting height	**1,8 – 4 m**
Optimal mounting height	**2 m**

CONNECTIVITY

Networking	**Nein**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Measured luminous flux 360°	**862 lm**
Colour temperature	**3000 K**
Colour rendering index	**80-89**
With illuminant	**Ja, STEINEL LED-System**
Illuminant	**LED nicht austauschbar**
Base	**Ohne**
LED cooling system	**Passive Thermo Control**
Soft light start	**No**

LIFETIME

LED lifetime max. °C	**50000 Std**
LED lifetime L70B50 25°C	**> 60000 Std**
Luminous flux decline per LM80	**L70B10**

SETTINGS

Twilight switch	**Ja**
Twilight setting	**2 – 1000 lx**
Time setting	**2 s – 70 Min.**
Base light function	**Nein**
Twilight setting teach	**No**

HOUSING & MATERIAL

Impact resistance	**IK03**
Protection class (IP)	**IP44**
Protection class	**II**
Ambient temperature	**von -20 bis zu 40 °C**
Housing material	**Kunststoff**
Cover material	**Kunststoff opal**
Mounting location	**Wand**
Application location	**Aussenbereich**
Mounting type	**Aufputz**
Application room	**Aussenbereich Rund ums Haus Terrasse / Balkon**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**3 Jahre**

CERTIFICATES & EPREL

Certificates	**EMV**
EPREL category	**Lichtquelle**


XLED curved S white

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841012083**
E-Nr. **941200269**

Illustrations

TECHNICAL DRAWINGS



120 x 160 x 107 mm

MOUNTING HEIGHT

1,8 – 4 m	2 m	4,00 m
BEREICH	OPTIMAL	MAX


XLED curved S white

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841012083**
E-Nr. **941200269**

Wiring Diagrams

WIRING DIAGRAM 1



XLED curved S white

SENSOR-SWITCHED LED FLOODLIGHT

EAN **4007841012083**
E-Nr. **941200269**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841012083
EAN	4007841012083
E-Number	941200269
Typ	**XLED curved S white**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss