

nefera P 4K

NEFERA C / P / W

neva
lux

Product code **220171**

- For universal use in office and school lighting, Traffic zones etc.
- Flat design and completely homogeneous illumination
- High quality finish
- Direct and indirect light distribution
- Very good glare control values (UGR<17)
- Dimmable DALI
- Housing Aluminium white

neva
lux

1200 x 260 x 30 mm



nefera P 4K

NEFERA C / P / W

Product code 220171

Technical Data

DIMENSIONS			
Dimensions L x W x H	1200 x 260 x 30 mm		
Suspension length	1500 mm		
ELECTRICAL			
Mains connection	200...240 V / 50 – 60 Hz		
Power	60 W		
Replaceable driver	Yes		
Type of wiring	Suitable for through wiring		
SENSOR TECHNOLOGY			
With motion detector	No		
With light sensor	No		
LIGHTING TECHNOLOGY			
Colour temperature	4000 K		
LED colour deviation	SDCM3		
Colour rendering index	80-89		
Illuminant		LED	
Luminous flux		6000 lm (Down 4000, Up 2000)	
Beam angle		Down 90°, Up 110°	
Luminaire luminous efficacy		100 lm/W	
Glare value		UGR < 19	
LIFETIME			
LED lifespan (25 °C)		50000 h	
SETTINGS			
DALI dimming		Yes	
With emergency light		No	
Suitable for light band configuration		No	
Direct/indirect ratio separately controllable		No	
Constant light output control		Yes	
HOUSING & MATERIAL			
Protection class (IP)		IP20	
Protection class		I	
Ambient temperature		-20...45 °C	
Housing material		Aluminum	
Cover material		Microprismatic acrylic glass	
Mounting type		Ceiling pendant	
Colour		white	
SCOPE OF DELIVERY & WARRANTY			
Manufacturer warranty		5 years	
CERTIFICATES & EPREL			
EPREL energy efficiency class		F	

nefera P 4K

NEFERA C / P / W

Product code **220171**

Accessories

ORDERING INFORMATION

Art.-Nr. 220171

Typ nefera P 4K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss