IS 2360 ECO 7m white

MOTION DETECTOR

EAN 4007841006556
E-Nr. 535954000

steinel

115 x 51 mm



IS 2360 ECO 7m white

MOTION DETECTOR

EAN 4007841006556
E-Nr. 535954000

Technical Data

IDENTIFICATION

Version	**Motion detectors**

DIMENSIONS

Dimensions Ø × H	**115 x 51 mm**

ELECTRICAL

Mains connection	**230 V / 50 – 60 Hz**
Power	**2000 W**
Switching output 1 resistive	**2000 W**
Fluorescent lamps ECG	**350 W**
Fluorescent lamps uncompensated	**500 VA**
Fluorescent lamps series-compensated	**500 VA**
Fluorescent lamps parallel-compensated	**500 VA**
Switching output 1 low-voltage halogen lamps	**1000 VA**
LED lamps < 2 W	**100 W**
LED lamps > 2 W < 8 W	**175 W**
LED lamps > 8 W	**350 W**
Capacitive load in µF	**132 µF**
Switching output 1 number of LED/fluorescent lamps	**50 pcs.**

SENSOR TECHNOLOGY

Max. mounting height	**4,00 m**
Sensor technology	**passive infrared**
Detection angle	**360 °**
Opening angle	**180 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**No**
Mechanical scalability	**No**
Radial range	**Ø 3 m (7 m²)**
Tangential range	**Ø 7 m (38 m²)**
Switching zones	**664 switching zones**
Mounting height	**2,00 – 4,00 m**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/master**
Networking quantity	**max 5 sensors**

LIGHTING TECHNOLOGY

Soft light start	**No**
Continuous light	**selectable**
Constant light regulation	**No**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**8 s – 35 Min.**
Base light function	**No**
Main light adjustable	**No**
Settings via	**Potentiometers**
With remote control	**No**
Twilight setting teach	**No**

HOUSING & MATERIAL

Protection class (IP)	**IP54**
Ambient temperature	**from -20 up to 50 °C**
Mounting location	**ceiling**
Application location	**Indoors Outdoors**
Mounting type	**Surface wiring**
Material	**Plastic**
Application room	**Indoors WC / washroom changing room corridor / aisle function room / ancillary room kitchenette multi-storey / underground car park outdoors stairwell warehouse**
Colour	**white**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**

CERTIFICATES & EPREL

Certificates	**VDE**


IS 2360 ECO 7m white

MOTION DETECTOR

EAN 4007841006556
E-Nr. 535954000

Illustrations

TECHNICAL DRAWINGS



115 x 51 mm

MOUNTING HEIGHT

2,00 – 4,00 m	2,8 m	4,00 m
BEREICH	OPTIMAL	MAX


IS 2360 ECO 7m white

MOTION DETECTOR

EAN 4007841006556
E-Nr. 535954000

Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

IS 2360 ECO 7m white

MOTION DETECTOR

EAN 4007841006556
E-Nr. 535954000

Highlights



UV-resistant plastic

IS 2360 ECO 7m white

MOTION DETECTOR

EAN **4007841006556**
E-Nr. **535954000**

Accessories

ORDERING INFORMATION

Art.-Nr.	006556
EAN	4007841006556
E-Number	535954000
Typ	**IS 2360 ECO 7m white**

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss