

RS PRO Q1 S neutralweiss silber



Product code **4007841007102**

E-Nr. **941339109**

- Including STEINEL LED system
- Intelligent LED cooling system
- Intelligent soft light start
- Optional basic lighting level 10 - 50 %
- Wireless interconnection with Remote Group Setting
- High-quality aluminium
- Optional remote control RC10
- Smart Remote remote control optional

neva
lux

56 x 331 x 331 mm



RS PRO Q1 S neutralweiss silber

Product code **4007841007102**
E-Nr. **941339109**

Technical Data

DIMENSIONS	
Dimensions L x W x H	56 x 331 x 331 mm
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	26 W
SENSOR TECHNOLOGY	
Max. mounting height	4,00 m
Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	5,8 GHz
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	160 °
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	No
Radial range	Ø 8 m (50 m²)
Tangential range	Ø 8 m (50 m²)
Mounting height	2,00 – 4,00 m
Optimal mounting height	2,5 m
CONNECTIVITY	
Networking	Yes
Type of networking	Master/master\nMaster/slave
Networking via	Wireless

LIGHTING TECHNOLOGY	
Measured luminous flux 360°	2920 lm
Colour temperature	4000 K
LED colour deviation	SDCM3
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Continuous light	selectable
LIFETIME	
LED lifetime max. °C	50000 h
LED lifetime L70B50 25°C	> 60000 h
Luminous flux decline per LM80	L70B10
SETTINGS	
Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 Min.
Base light function	Yes
Base light function time	10/30 min, all night
Main light adjustable	50 - 100 %
Functions	Group parameterisation\nManual ON / ON-OFF\nMaster/slave override\nNeighbouring group function

Settings via	switches\nPotentiometers\nRemote control\nSmart Remote
With remote control	No
Twilight setting teach	Yes
Base light function in percent	10 – 50 %
Base light function percent from	10 %
HOUSING & MATERIAL	
Impact resistance	IK03
Protection class (IP)	IP20
Protection class	II
Ambient temperature	-10 – 50 °C
Housing material	Aluminium
Cover material	Plastic, opal
Mounting location	ceiling wall
Application location	Indoors
Mounting type	Surface wiring
Application room	Indoors WC / washroom changing room corridor / aisle function room / ancillary room kitchenette outdoors stairwell
Colour	Silver
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years

RS PRO Q1 S neutralweiss silber

Product code **4007841007102**
E-Nr. **941339109**

Illustrations

MOUNTING HEIGHT

2,00 – 4,00 m BEREICH	2,5 m OPTIMAL	4,00 m MAX
--------------------------	------------------	---------------

RS PRO Q1 S neutralweiss silber

Product code **4007841007102**
E-Nr. **941339109**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841009151	Smart Remote	Accessory
 4007841007645	RC10 für RS PRO Q1	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841007102

E-Number

941339109

Typ

RS PRO Q1 S neutralweiss silber

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss