

LED Insert B600 3K DALI 60°

INSERT B



Product code **221714**

- For professional refurbishment of luminaires with T5 or T8 fluorescent tubes
- Universal use for all lighting tasks
- Excellent efficiency and durability
- Connect accessories available with powerful IoT lighting control for next-generation lighting projects (swarm function, grouping, cleaning light, etc.)
- Magnetic attachment for easy and quick mounting
- 2 power classes, 5 lengths, 3 optics and 3 light colors available

neva
lux

581 x 32 x 24 mm



LED Insert B600 3K DALI 60°

INSERT B

Product code 221714

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Variant	Narrow beam 60°	Colour temperature	3000 K	Protection class (IP)	IP20
DIMENSIONS		Colour rendering index	80-89	Protection class	I
Dimensions L x W x H	581 x 32 x 24 mm	Illuminant	LED	Ambient temperature	-25...55 °C
ELECTRICAL		Luminous flux	2306 lm	Housing material	Aluminum
Mains connection	220...240 V / 50 – 60 Hz	Beam angle	60°	Cover material	PMMA
Power	14.6 W	Luminaire luminous efficacy	158 lm/W	Mounting type	lighting insert
Replaceable driver	Yes	LIFETIME		Colour	Aluminum
Type of wiring	Suitable for through wiring	LED lifespan (25 °C)	72000 h	SCOPE OF DELIVERY & WARRANTY	
LED rated current	300 mA	SETTINGS		Manufacturer warranty	5 years
SENSOR TECHNOLOGY		DALI dimming	Yes	CERTIFICATES & EPREL	
With motion detector	No	With emergency light	No	EPREL energy efficiency class	C
		Suitable for light band configuration	Yes		

LED Insert B600 3K DALI 60°

INSERT B

Product code 221714

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221935	Connect Smartlink HF3 Astra PSU	Motion detector
 221618	Emergency Package 1h (50V/3.5W)	Emergency lighting
 221965	LED Insert M-Set 2SK	Mounting kit
 221966	LED Insert M-Set 2S	Mounting kit
 221968	LED Insert B M-Set K	Mounting kit

ORDERING INFORMATION

Art.-Nr.221714

TypLED Insert B600 3K DALI 60°

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss