

IS 345 LiveLink - Unterputz eckig

neva
lux

Product code 4007841049423

E-Nr. 535955267

neva
lux

94 x 94 x 78 mm



IS 345 LiveLink - Unterputz eckig

Product code 4007841049423
E-Nr. 535955267

Technical Data

IDENTIFICATION					
Variant	LiveLink - concealed installation, square	Electronic scalability	No	With remote control	No
Version	Motion detectors	Mechanical scalability	No	Twilight setting teach	Yes
Model	LiveLink	Radial range	12 x 6 m (72 m²)	HOUSING & MATERIAL	
DIMENSIONS		Tangential range	23 x 6 m (138 m²)	Protection class (IP)	IP20
Dimensions L x W x H	94 x 94 x 78 mm	Switching zones	280 switching zones	Ambient temperature	-20 – 50 °C
ELECTRICAL		Mounting height	2,50 – 5,00 m	Mounting location	ceiling
Mains connection	230 V, 50 / 60 Hz	Optimal mounting height	2,8 m	Application location	Indoors Outdoors
Supply voltage detail	DALI bus	CONNECTIVITY		Mounting type	Concealed wiring
Livelink values	Light level, Motion detection	Networking	Yes	Material	Plastic
SENSOR TECHNOLOGY		Number of DALI participants	3	Colour	white
Sensor technology	passive infrared	LIGHTING TECHNOLOGY		RAL colour	9003
Detection angle	360 °	Constant light regulation	No	SCOPE OF DELIVERY & WARRANTY	
Opening angle	45 °	SETTINGS		Manufacturer warranty	5 years
Sneak-under protection	Yes	Twilight setting	2 – 1000 lx	OTHER	
Segment-by-segment masking	Yes	Time setting	5 sec – 15 min	Application, location, room	corridor, aisle, underground car park, multi-storey car park
		Base light function	No		

IS 345 LiveLink - Unterputz eckig

Product code **4007841049423**
E-Nr. **535955267**

Illustrations

MOUNTING HEIGHT

2,50 – 5,00 m BEREICH	2,8 m OPTIMAL
--------------------------	------------------

IS 345 LiveLink - Unterputz eckig

Product code **4007841049423**

E-Nr. **535955267**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841049423
E-Number	535955267
Typ	IS 345 LiveLink - Unterputz eckig
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	