

RS PRO LED R1 neutralweiss weiss

neva
lux

Product code **4007841033354**

- Including STEINEL LED system
- Optional basic lighting level 20 %
- Intelligent soft light start
- Interconnectable by cable

neva
lux

270 x 70 mm



RS PRO LED R1 neutralweiss weiss

Product code 4007841033354

Technical Data

IDENTIFICATION		Electronic scalability		Yes	LIFETIME	
Variant	Neutral white white	Mechanical scalability		No	LED lifetime max. °C	50000 h
DIMENSIONS		CONNECTIVITY			Luminous flux decline per LM80	L70B10
Dimensions Ø x H	270 x 70 mm	Networking		Yes	SETTINGS	
ELECTRICAL		Type of networking		Sensor/slave	Twilight switch	Yes
Mains connection	220 – 240 V , 50 / 60 Hz	Networking quantity		10 lights max.	Twilight setting	2 – 2000 lx
Power	11 W	LIGHTING TECHNOLOGY			Time setting	5 sec – 15 min
Switching output 1 resistive	800 W	Colour temperature		4000 K	HOUSING & MATERIAL	
SENSOR TECHNOLOGY		LED colour deviation		SDCM3	Impact resistance	IK00
Sensor technology	High frequency	Colour rendering index		80-89	Protection class (IP)	IP20
Transmission power	< 1 mW	With illuminant		Yes, STEINEL LED system	Protection class	II
With motion detector	Yes	Illuminant		LED cannot be replaced	Ambient temperature	-10 – 50 °C
Detection	also through glass, wood and stud walls	Base		without	Housing material	Plastic
Detection angle	360 °	LED cooling system		Passive Thermo Control	Cover material	Plastic, opal
Opening angle	160 °	Soft light start		Yes	SCOPE OF DELIVERY & WARRANTY	
		Continuous light		selectable, 4h	Manufacturer warranty	5 years
		Luminous flux		950 lm		

RS PRO LED R1 neutralweiss weiss

Product code 4007841033354

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841033354
Typ	RS PRO LED R1 neutralweiss weiss
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	