

sensIQ inox

neva
lux

Product code 4007841029586

- 4x pyro system
- Suitable for mounting on ceilings
- UV-resistant plastic
- Remote control RC9 included
- Including corner wall mount
- Smart Remote remote control optional

neva
lux

144 x 113 x 172 mm



Technical Data

IDENTIFICATION	
Variant	inox
Version	Motion detectors
Type of accessory	Corner adapter
DIMENSIONS	
Dimensions L x W x H	144 x 113 x 172 mm
ELECTRICAL	
Mains connection	220 – 240 V , 50 / 60 Hz
Switching output 1 resistive	2500 W
Switching output 1 number of LED/fluorescent lamps	8 pcs.
SENSOR TECHNOLOGY	
Sensor technology	passive infrared
Detection angle	300 °
Opening angle	90 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes

Electronic scalability	No
Mechanical scalability	Yes
Range detail	Reach adjustable from 2 - 20 m in 3 directions (100° in each)
Radial range	r = 4 m (42 m²)
Tangential range	r = 20 m (1047 m²)
Switching zones	1360 switching zones
Mounting height	2,00 – 5,00 m
Optimal mounting height	2 m
CONNECTIVITY	
Networking	Yes
LIGHTING TECHNOLOGY	
Constant light regulation	No
SETTINGS	
Twilight setting	2 – 2000 lx
Time setting	5 sec – 15 min
Base light function	No

With remote control	Yes
Twilight setting teach	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP54
Ambient temperature	-20 – 50 °C
Mounting location	ceiling corner wall
Application location	Indoors Outdoors
Mounting type	Surface wiring
Material	Plastic
Colour	Stainless steel
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
Certificates	VDE
OTHER	
Application, location, room	multi-storey car park, underground car park

sensIQ inox

Product code **4007841029586**

Illustrations

MOUNTING HEIGHT

2,00 – 5,00 m BEREICH	2 m OPTIMAL
---	-----------------------------------

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841007638	Fernbedienung RC9	Other
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841029586

Typ

sensIQ inox

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss