

IS 345 LiveLink - Aufputz eckig

neva
lux

Product code 4007841049416

E-Nr. 535941109

neva
lux

95 x 95 x 65 mm



IS 345 LiveLink - Aufputz eckig

Product code **4007841049416**
E-Nr. **535941109**

Technical Data

IDENTIFICATION					
Variant	LiveLink - surface-mounted, square	Segment-by-segment masking	Yes	Base light function	No
Version	Motion detectors	Electronic scalability	No	With remote control	No
Model	LiveLink	Mechanical scalability	No	Twilight setting teach	Yes
DIMENSIONS				HOUSING & MATERIAL	
Dimensions L x W x H	95 x 95 x 65 mm	Radial range	12 x 6 m (72 m²)	Protection class (IP)	IP54
ELECTRICAL		Tangential range	23 x 6 m (138 m²)	Ambient temperature	-20 – 50 °C
Mains connection	230 V, 50 / 60 Hz	Switching zones	280 switching zones	Mounting location	ceiling
Supply voltage detail	DALI bus	Mounting height	2,50 – 5,00 m	Application location	Indoors Outdoors
Livelihood values	Light level, Motion detection, Presence detection	Optimal mounting height	2,8 m	Mounting type	Surface wiring
SENSOR TECHNOLOGY		CONNECTIVITY		Material	Plastic
Sensor technology	passive infrared	Networking	Yes	Colour	white
Detection angle	360 °	Number of DALI participants	3	RAL colour	9003
Opening angle	45 °	LIGHTING TECHNOLOGY		SCOPE OF DELIVERY & WARRANTY	
Sneak-under protection	Yes	Constant light regulation	No	Manufacturer warranty	5 years
		SETTINGS		OTHER	
		Twilight setting	2 – 1000 lx	Application, location, room	corridor, aisle, underground car park, multi-storey car park
		Time setting	5 sec – 15 min		

IS 345 LiveLink - Aufputz eckig

Product code 4007841049416
E-Nr. 535941109

Illustrations

MOUNTING HEIGHT

2,50 – 5,00 m BEREICH	2,8 m OPTIMAL
--------------------------	------------------

IS 345 LiveLink - Aufputz eckig

Product code **4007841049416**
E-Nr. **535941109**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841049416
E-Number	535941109
Typ	IS 345 LiveLink - Aufputz eckig
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	